



High firmness and stability of cookware

The Series 40 EasyCook gas hob offers a large and stable cooking surface for pots and pans of all sizes. Easily place and move everything around on the spacious hob, even when you're cooking on multiple burners at once.

Product Benefits & Features

Perfect Flame Regulation, for perfect temperature

The hob's responsive gas taps feature Perfect Flame Regulation. Giving you complete control over the temperature you want to cook your favourite dishes with.

- Hob type: Gas
- Rotary knob controls
- Controls position: Front Right
- Left front zone: Rapid Burner, 3000W/100mm
- Left rear zone: Semi Rapid Burner, 2000W/70mm
- Middle front zone: No, 0W/0mm
- Middle rear zone: No, 0W/0mm
- Right front zone: Auxiliary Burner, 1000W/54mm
- Right rear zone: Semi Rapid Burner, 2000W/70mm
- Gas conversion kit
- Main colour: Stainless Steel

Easy cooking, with Integrated Ignition

Get cooking quickly with Integrated Ignition. To activate the cooking zones, simply press the temperature knob down and turn.

Gas Safety built in

The built-in Gas Safety feature offers peace of mind in the kitchen. If the flame were to go out accidentally while you're cooking, the hob will automatically switch the gas off, too.

SlimDesign hob, for the modern kitchen

The stainless-steel SlimDesign hob barely rises above the counter top, for a seamless kitchen finish. And its raised edge will prevent any spillages from running onto surrounding surfaces.

Product Specification

Product Installation	Built_In	Gas category	I12H3+
Product Typology	Gas_Hob	Frequency	50-60
Product Classification	Core	Voltage	220-240
Installation	Independent	Cord length external	1.1
Size	60	Type of plug	UK Moulded
Hob type	Gas	Connector type	Conic gas elbow
Design family	Yellow	Left front - Cooking zone	Rapid Burner
Main colour	Stainless Steel		
Control Panel material	Stainless Steel		
Knobs colour	Black		
Top Control Place	Front Right		
Type of controls	Knobs		
Control function	No		
Other comments categorisation	copy of PNC 949 640 626 with black full plastic Zanussi knobs		
Width mm	594		
Depth mm	510		
Built in height mm	40		
Width cutting	560		
Depth cutting	480		
Fastening	Fixing Clamps		
Gas original	G20 (2H) 20 mbar		
Gas replacement 2	G30/G31 (3+) 28-30/37 mbar, With Additional Injectors		
Gas replacement 3	No		