



Damplas double-sided jointing tape

- BBA approved (as part of DPM, Amber 2 and Radon Gas jointing system)
- Easy to use with excellent adhesion
- Excellent methane gas resistance, tested to ISO15015-1, achieves 0.07 ml/ linear metre/ day

DESCRIPTION

Dampas Double-sided Jointing Tape is a high performance blue butyl mastic tape with adhesive to both sides, supplied in 50mm x 10m rolls for membrane joints and Dampas CPT Plus Jointing tape and 100mm x 10m for damp proof course joints and gas membrane systems.



APPLICATION

Dampas Double-sided Jointing type is designed for use in bonding overlaps in Dampas membrane, gas membrane and DPC systems.

JOINTING PROCEDURE

Always ensure that the membrane and/or DPC is clean, dust free and dry at the time of jointing. Adjacent sheets must be overlapped by a minimum of 150mm. Bond together using Damplas Double Sided Jointing tape, the lap should be sealed using Damplas Single Side jointing tape. If the membrane has been damaged it should be patched with sheets of identical thickness lapped at least 150mm beyond the limits of the puncture and bonded with Damplas Double-sided Jointing Tape and sealed with Damplas Single-sided Jointing Tape.

STORAGE AND HANDLING

Store in a warm dry place until required for use.



NDC Polipak Ltd
1 Garratts Lane
Cradley Heath
B64 5RE

t +44 (0) 121 561 6700
f +44 (0) 121 559 0230
enquiries@ndcpolipak.com
www.ndcpolipak.com

