

Declaration of Performance (DoP)

No: UKCADOP2021-1-Wickes – The Premium Hybrid

1. Unique identification code of the product - type:

WICKES – THE PREMIUM HYBRID (White, Black & Grey)

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):

For batch number; see product packaging.

3. Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:

4.

BS EN15651-1: F-EXT INT: Sealant for façade for external or interior application.
BS EN15651-3: S: Sealants for sanitary joints.

5. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):

Wickes Building Supplies Limited, Vision House, 19 Colonial Way, Watford, WD24 4JL.

6. Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):

Not applicable.

7. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

8. In case of declaration of performance concerning a construction product covered by a harmonised standard:

BS EN15651-F-EXT INT
BS EN15651-S

The approved body 4Ward Testing Ltd, identification number 0307 performed initial type tests under system 3 and issued a report.

9. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not Applicable.

10. Declared Performance

BS EN 15651-1: F-EXT INT Pre-Conditioning: Method A. Substrate: Mortar – without primer.		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (BS EN13501)	NPD	
Release of Chemicals	See product safety data sheet	
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-1: 2012
Loss of volume (ISO10563)	≤ 10%	EN 15651-1: 2012
Elongation at break (ISO8339)	NPD	EN 15651-1: 2012
BS EN 15651-3: S		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (BS EN13501)	NPD	
Release of Chemicals	See product safety data sheet	
Resistance to flow (ISO7390)	≤ 3mm	EN 15651-3: 2012
Loss of volume (ISO10563)	≤ 10%	EN 15651-3: 2012
Elongation at break (ISO10591)	NPD	EN 15651-3: 2012
Microorganisms: intensity of growth	2	EN 15651-3: 2012

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

11. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for on behalf of the manufacturer by



Name: Jimmy Walsh

Date: 22/10/2021

<p>UK CA</p> <p>2538</p>
<p>Wickes Building Supplies Limited, Vision House, 19 Colonial Way, Watford, WD24 4JL.</p> <p>21</p> <p>Reference No: UKCADOP2021-1-Wickes – The Premium Hybrid</p>
<p><u>WICKES – The Premium Hybrid</u> BS EN 15651-1: F-EXT INT BS EN 15651-3: S2 Pre-Conditioning: Method A. Substrate: Mortar – without primer.</p>
<p>EN 15651-1: F-INT-EXT: Sealant for façade for exterior and interior application. EN15651-3: S: Sealants for sanitary joints. Reaction to Fire NPD Resistance to flow ≤3mm Loss of volume ≤10% Elongation at break NPD Tensile properties at maintained extension after immersion in water NPD Microorganisms intensity of growth 2</p>