

QUICK DRY OUTDOOR WOODSTAINS

Page: 1

Compilation date: 07/05/2015

**Revision date: 21/10/2020** 

Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: QUICK DRY OUTDOOR WOODSTAINS

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

## 1.4. Emergency telephone number

**Emergency tel:** .+44(0)2084504666 (Office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; -: EUH208

Most important adverse effects: Contains texanol. May produce an allergic reaction. Causes serious eye irritation.

## 2.2. Label elements

Label elements:

**UFI:** VX2E-YUT8-P103-Y4H6

**Hazard statements:** EUH208: Contains texanol. May produce an allergic reaction.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

## QUICK DRY OUTDOOR WOODSTAINS

Page: 2

contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

## **Hazardous ingredients:**

### 3-BUTOXYPROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
225-878-4	5131-66-8	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315	4.500%	
TEXANOL					
-	25265-77-4	-	Aquatic Chronic 3: H412; Skin Sens. 1: H317	0.980%	
AMMONIA SOLUTION					
-	H335; A		Skin Corr. 1C: H314; STOT SE 3: H335; Aquatic Acute 1: H400; STOT SE 3: H336	0.200%	

### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

## QUICK DRY OUTDOOR WOODSTAINS

Page: 3

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

## QUICK DRY OUTDOOR WOODSTAINS

Page: 4

## 8.1. Control parameters

Workplace exposure limits: No data available.

**DNEL/PNEC Values** 

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Viscous

Boiling point/range°C: 100 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: >93 Part.coeff. n-octanol/water: No data available.

**Autoflammability°C:** No data available. **Vapour pressure:** No data available.

**Relative density:** 1.017-1.027 @ 20 C **pH:** 7.5 - 8.0

VOC g/l: No data available.

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## QUICK DRY OUTDOOR WOODSTAINS

Page: 5

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

#### **Hazardous ingredients:**

#### 3-BUTOXYPROPAN-2-OL

SKN	RBT	LD50	3100	ma/ka	
				3 3	

### Relevant hazards for product:

Hazard	Route	Basis	
Serious eye damage/irritation	OPT	Hazardous: calculated	

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

## QUICK DRY OUTDOOR WOODSTAINS

Page: 6

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

### 14.1. UN number

**UN number: NOT CLASSIFIED** 

## 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

# 14.4. Packing group

## 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

### **Section 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

## Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains texanol. May produce an allergic reaction.

## QUICK DRY OUTDOOR WOODSTAINS

Page: 7

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.