

SuperCLOSE

Easy Fit

Insulated Cavity Closer



- ✓ **Easy Fit - With Simple Cut to Size Indicators**
- ✓ **Fully Ridged uPVC Cavity Closer**
- ✓ **Building Regulations Compliant**
- ✓ **Fully Certified**



- ✓ **Exceeds Building Regulations Minimum Thermal Resistance**
- ✓ **Suitable For Use in both New Build and Refurbishments**



Two profiles available to fit: 50-100mm cavities & 100-150mm cavities

SuperCLOSE can be installed in a variety of ways:

Tack to window frame if built in.

Built-in as work progresses friction fitting.

SuperCLOSE can be installed after the reveal has been constructed by fixing the inner leaf using grab adhesive.

Vertical Jointing

If required, sections of SuperCLOSE can be jointed to minimise waste.

All joints must be tightly butted - 45 degree downwards towards the outer leaf.


This will stop potential water penetration.

Corner Jointing

When jointing horizontal to vertical, trim both PVC flanges and allow the vertical to extend below the horizontal - this stops water ingress.


1

Measure the opening of window/door




2

Cut profile to required length




3

Measure cavity opening




4

Cut insulation to required width.



5

Fix in place with clout nails or grab adhesive.



Product	Insulation Width	Length	Thickness	Pack Qty	Pallet Qty	Pack Weight
SC100	50-100mm	2.4m	20mm	10	400	10kg
SC150	100-150mm	2.4m	20mm	10	300	14kg

Essential Characteristics	Performance	Technical Standard
Thermal Conductivity	0.034 W/mK	EN 13163
Minimum Thermal Resistance	0.877 m ² K/W	IP 1/06

Email: sales@superfoil.co.uk
SuperFOIL.co.uk



SuperCLOSE

