

GAS FRAMING NAILER



## 360Xi

TOOL PRODUCT CODE:  
**019700**

The 360Xi framing nailer is light and perfectly balanced to guarantee a great performance for multiple applications. A high performing lithium battery and a weatherproof fuel cell ensures the tool will run all day, every day no matter the challenge.

### IDEAL USERS

Carpenters or Joiners working on New Build and Renovation projects.



FEATURE



BENEFIT

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Unbeatable power to weight ratio, the most powerful Paslode framing nailer: 105 Joules</li> <li>• Light and perfectly balanced with a re-engineered grip and new battery position</li> <li>• Quick release magazine</li> <li>• Fast charging, high performing Lithium battery (200 shots in just 2 minutes)</li> <li>• Cold weather performance</li> </ul> | <ul style="list-style-type: none"> <li>• Able to drive 90mm Ring Shank nails into the hardest substrates</li> <li>• Ensures extra comfort and convenience, with reduced fatigue, guaranteeing all day productivity</li> <li>• Designed to eliminate nail jams</li> <li>• Delivers up to 13,000 shots per charge, equates to over 5 nail fuel packs</li> <li>• Allows user to work down to -15°C</li> </ul> |
|---|--|

### DID YOU KNOW:

The Paslode No-mar Cladding probe is available as an interchangeable accessory. Product Code: 019783



BATTERY PRODUCT CODE:  
**018880**

FUEL CELL PRODUCT CODE:  
**300348**



CONSUMABLES

EN ISO11148-13  
European Safety Standard

BS 5534  
British Standard

### EUROCODE 5 SERVICE CLASS

All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

### CORROSION REQUIREMENTS OUTLINED IN EC5

	Service Class 1 INDOORS	Service Class 2 INDOORS NOT HEATED, OUTDOORS PROTECTED	Service Class 3 OUTDOORS, EXPOSED TO WEATHER
<b>BRIGHT</b>			
<b>ELECTRO GALV ≥ 12µm and GALV-PLUS® ≥ 15µm</b>			
<b>HOT DIPPED GALVANISED ≥ 55µm</b>			
<b>STAINLESS STEEL - A2 (AISI 304) &amp; A4 (AISI 316)</b>			

All Paslode nails are hexavalent chromium, cadmium and lead free. Technical documentation available via the website - [www.paslode.co.uk](http://www.paslode.co.uk)

- 360Xi requires Paslode 2.8 or 3.1mm RounDrive® nails. Available in sizes from 51 - 90mm
- Capable of firing NailScrews®

### 360Xi NAIL SELECTION GUIDE

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS										
				Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
51 x 2.8mm Ring	3	3300	141083	●										
63 x 2.8mm Ring	3	3300	141078	●										
75 x 3.1mm Ring	2	2200	141081		●	●								
90 x 3.1mm Smooth	2	2200	141076		●	●	●							
90 x 3.1mm Ring	2	2200	141082		●	●								
50 x 2.8mm NailScrew*	1	1100	141084								●			●
51 x 2.8mm Ring	3	3300	141075								●			
51 x 2.8mm Ring	1	1100	141080								●			
63 x 2.8mm Ring	3	3300	141071								●			
63 x 2.8mm Ring	1	1100	141079								●			
63 x 3.1mm Ring	2	2200	141073								●			
65 x 2.8mm NailScrew*	1	1100	141086								●			●
75 x 2.8mm NailScrew*	1	1100	141085								●			●
75 x 3.1mm Ring	2	2200	141072			●	●	●			●			●
90 x 3.1mm Smooth	2	2200	141070								●			
90 x 3.1mm Smooth	1	1100	141077								●			
90 x 3.1mm Ring	2	2200	141074								●			
63 x 2.8mm Ring	3	3300	140631								●			●
63 x 3.1mm Ring	2	2200	140625								●			●
75 x 3.1mm Ring	2	2200	140630								●			●
90 x 3.1mm Smooth	2	2200	140629								●			●
90 x 3.1mm Ring	2	2200	140628								●			●
50 x 2.8mm NailScrew A2	1	1100	140633								●			●
51 x 2.8mm Ring A2	1	1100	140624								●			●
63 x 2.8mm Ring A2	1	1100	140626								●			●
63 x 2.8mm Ring A4	1	1100	140632								●			●
80 x 3.1mm Ring A2	1	1100	140627								●			●

\*ELECTRO GALV ≥ 12µm

- BRIGHT (INDOOR, SERVICE CLASS 1.)
- ELECTRO GALV ≥ 12µm / GALV-PLUS® ≥ 15µm (INDOOR NOT HEATED, OUTDOOR PROTECTED, SERVICE CLASS 2.)
- HOT DIPPED GALV (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)
- STAINLESS STEEL A2-304 / A4-316 (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)