

GAS FRAMING NAILER



## IM350+

TOOL PRODUCT CODE:  
**905900**

The IM350+ is a long serving Paslode framing nailer offering reliable technology for the past 30 years. Proven unrivalled gas technology guarantees tool performance and reliability.

### IDEAL USERS

Carpenter, Roofer or General Builder working on New Build and Renovation projects.



#### FEATURE



#### BENEFIT

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>● Powerful framing nailer: 82 Joules</li> <li>● Multi-angled teeth nose probe</li> <li>● Excellent power, weight and balance ratio</li> <li>● Fast charging, high performing Lithium battery (200 shots in just 2 minutes)</li> </ul> | <ul style="list-style-type: none"> <li>● Suitable for versatile framing applications</li> <li>● Increases fixing accuracy</li> <li>● Reduced fatigue and increased productivity</li> <li>● Delivers up to 9,000 shots per charge, equates to over 4 nail fuel packs</li> </ul> |
|--|--|



**! DID YOU KNOW:**  
1 lithium battery is compatible for 7 Paslode tools.

BATTERY PRODUCT CODE:  
**018880**

FUEL CELL PRODUCT CODE:  
**300346**



CONSUMABLES

EN ISO11148-13  
European Safety Standard

BS 5534  
British Standard

### EUROCODE 5 SERVICE CLASS

All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

### CORROSION REQUIREMENTS OUTLINED IN EC5

	Service Class 1 INDOORS	Service Class 2 INDOORS NOT HEATED, OUTDOORS PROTECTED	Service Class 3 OUTDOORS, EXPOSED TO WEATHER
BRIGHT			
ELECTRO GALV ≥ 12µm and GALV-PLUS® ≥ 15µm			
HOT DIPPED GALVANISED ≥ 55µm			
STAINLESS STEEL - A2 (AISI 304) & A4 (AISI 316)			

All Paslode nails are hexavalent chromium, cadmium and lead free. Technical documentation available via the website - [www.paslode.co.uk](http://www.paslode.co.uk)

- IM350+ tool requires Paslode 2.8 or 3.1mm clipped nail available in sizes from 51 - 90mm
- Wide range of Paslode Nail fuel packs available

### IM350+ NAIL SELECTION GUIDE

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS											
				Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing	
51 x 2.8mm Ring	3	3300	141202	●											
63 x 2.8mm Ring	3	3300	141208												
75 x 3.1mm Ring	2	2200	141226		●	●									
90 x 3.1mm Smooth	2	2200	141233		●	●	●								
51 x 2.8mm Ring	3	3300	141204									●			
51 x 2.8mm Ring	1	1100	141256									●			
63 x 2.8mm Ring	3	3300	141210									●			
63 x 2.8mm Ring	1	1100	141259									●			
63 x 3.1mm Ring	2	2200	141221									●			
75 x 3.1mm Ring	2	2200	141227			●	●	●							
90 x 3.1mm Smooth	2	2200	141234					●							
50 x 2.8mm Ring	3	3300	141205											●	●
63 x 2.8mm Ring	3	3300	141211											●	
63 x 3.1mm Ring	2	2200	141222											●	
75 x 3.1mm Ring	2	2200	141228											●	
75 x 3.1mm Ring	1	1100	141265											●	
90 x 3.1mm Smooth	2	2200	141235											●	
90 x 3.1mm Smooth	1	1100	141267											●	
90 x 3.1mm Unilock	2	2200	141236											●	
51 x 2.8mm Ring A2	1	1100	141257											●	●
63 x 2.8mm Ring A2	1	1100	141261											●	
80 x 3.1mm Ring A2	1	1100	141266											●	

- BRIGHT (INDOOR, SERVICE CLASS 1.)
- GALV-PLUS (INDOOR NOT HEATED, OUTDOOR PROTECTED, SERVICE CLASS 2.)
- HOT DIPPED GALV (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)
- STAINLESS STEEL A2-304 / A4-316 (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)