



### Boiling on the hob made easy

The Series 60 BoilAssist hob looks after water on your behalf. When it detects rising bubbles in the pan, it will automatically adjust the temperature, reducing water to a safe, gentle simmer. Which means you can concentrate on the rest of your meal without distraction.

## Product Benefits & Features

### Boiling water kept under control, with Boil Sensor

When water is about to reach its boiling point, Boil Sensor will detect the rising bubbles and reduce the induction hob's temperature. So hot water never boils over.

### Automatic fans, with Hob2Hood

With Hob2Hood technology, the fans overhead will adjust on their own based on your hob's settings. As you cook, the fans will speed up or slow down to match any temperature changes you make. So you can forget about hood settings, and focus on your tasty meal.

### Swipe for temperature control with Direct Touch

Direct Touch control is built for simplicity, letting you change each hob's temperature setting with your fingertip. Just slide it over the touch-sensitive panel.

### No overcooking with Timer function

When the timer you've set runs out, the hob will automatically switch off the heat. It can be set to a maximum limit of 1.5 hours, which means that even if you're concentrating on a few different things at once, your meal will be ready when you are.

### Intense heat when you need it, with PowerBoost

The PowerBoost function is designed for intense heat on demand. Boil water quicker than the kettle, or turn up the temperature under your griddle pan for searing and sealing steaks. Built for convenience, to make preparing your favourite meals easier.

- Hob type: Induction
- Frameless hob
- Sliding touch control technology
- Controls position: Front Middle
- Illuminated controls
- Digital indications for each zone
- Induction zones with power booster function
- Pot detection
- Left front zone: Induction, 2300/3200W/210mm
- Left rear zone: Induction, 2300/3200W/210mm
- Middle front zone: No, 0W/0mm
- Middle rear zone: No, 0W/0mm
- Right front zone: Induction, 2300/3200W/210mm
- Right rear zone: Induction, 2300/3200W/210mm
- Automatic fast heating up
- Key-lock function
- Child safety lock function
- Acoustic signal
- Timer function
- Easy installation thanks to snap-in system
- Main colour: Black

## Product Specification

|                        |   |                      |                 |
|------------------------|---|----------------------|-----------------|
| Product Installation   | Built_In  | Fastening            | Snap in System  |
| Product Typology       | Electric_Hob  | Gas original         | No              |
| Product Classification | Performance   | Gas replacement 2    | No              |
| Installation           | Independent   | Gas replacement 3    | No              |
| Size                   | 80  | Gas category         | No              |
| Hob type               | Induction Full  | Frequency            | 50-60           |
| Design family          | Yellow  | Voltage              | 220-240V/400V2N |
| Main colour            | Black   | Cord length external | 1.5             |
| Control Panel material | No  | Type of plug         | No              |
| Frame type             | Frameless Square  |                      |                 |
| Frame material         | No  |                      |                 |
| Knobs colour           | No  |                      |                 |
| Top Control Place      | Front Middle  |                      |                 |
| Type of controls       | Kite 9 steps  |                      |                 |
| Control function       | 3 step residual heat, Acoustic signal, Automatic heating-up, BoilAssist, Booster, Child-lock, Hob-hood connection, Key-lock function, Minute minder, Pause, Timer |                      |                 |
| Width mm               | 780   |                      |                 |
| Depth mm               | 520   |                      |                 |
| Built in height mm     | 44  |                      |                 |
| Width cutting          | 750   |                      |                 |
| Depth cutting          | 490   |                      |                 |
| Radius cutting         | 5   |                      |                 |

