

N 90, Gas hob, 90 cm, Ceramic
T29TS79N0



COOKING PASSION SINCE 1877



The gas hob with heat-resistant ceramic glass surface and adjustable FlameSelect control.

- ✓ Ceramic Glass Surface - extremely easy-to-clean surface.
- ✓ FlameSelect® – Gain ultimate control of your flame.
- ✓ Pan Supports - continuous cast-iron pan supports for maximum stability and cooking convenience.
- ✓ Biomethane ready – Power your hob with renewable biomethane gas.
- ✓ Sword Knobs - a better feel and easier to operate, the new knob in an attractive design.



Features

Technical Data

Product name/family : gas hob w integrated controls
Construction type : Built-in
Energy input : Gas
Total number of positions that can be used at the same time : 5
Type of control setting devices : sword knobs
Required niche size for installation (HxWxD) : 45 x 850-852 x 490-502 mm
Width of the appliance : 918 mm
Dimensions : 59 x 918 x 546 mm
Dimensions of the packed product (HxWxD) : 165 x 1116 x 659 mm
Net weight : 18.3 kg
Gross weight : 22.0 kg
Residual heat indicator : without
Location of control panel : Hob front
Basic surface material : Ceramic
Color of surface : Black, Stainless steel
Color of frame : Black, Stainless steel
Approval certificates : CE, E17D UKCA marking, Eurasian
Length of electrical supply cord : 150 cm
Knob Material : Plastic
Sealed Burners : No
Type of pan support : Elongated cast iron pan support
Power of 4th heating element (kW) : 1.1 kW
Power of 5th heating element (kW) : 2.8 kW
Connection rating : 1 W
Gas connection rating : 13800 W
Fuse protection : 3 A
Voltage : 220-240 V
Frequency : 50; 60 Hz
Main colour of product : Black
Energy input : Gas
Gas type : Nat gas H/E/(L) 20 (25) mbar
Alternative gas type : Liquid gas G30,31 28-30/37mbar
Approval certificates : CE, E17D UKCA marking, Eurasian
Plug type : no plug
Appliance Dimensions (h x w x d) (in) : + x x
Dimensions of the packed product : 6.49 x 25.94 x 43.93
Net weight : 40.000 lbs
Gross weight : 49.000 lbs
Total number of positions that can be used at the same time : 5
Length of electrical supply cord : 150 cm
Required niche size for installation (HxWxD) : 45 x 850-852 x 490-502 mm
Dimensions : 59 x 918 x 546 mm
Dimensions of the packed product (HxWxD) : 165 x 1116 x 659 mm
Net weight : 18.3 kg
Gross weight : 22.0 kg

Optional accessories

Z2402X0
Z2480X0



Features

Design

- ceramic glass surface, black
- Bevelled design, stainless steel
- black cast iron pan supports with protective rubber feet
- Low profile burner: elegant burner design

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Pan supports dishwasher safe: clean without effort in the dishwasher.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: Wok burner up to 6.1 KW (depending on gas type)
- Center front: Standard burner up to 1.9 KW (depending on gas type)
- Center rear: Economy burner up to 1.1 KW (depending on gas type)
- Right rear: High speed burner up to 2.8 KW (depending on gas type)
- Right front: Standard burner up to 1.9 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
NG H/E 20mbar, E+ 20/25mbar
Natural gas H 25 mbar (HU)
Natural gas L 25 mbar (NL)
Liquid gas G30,31 28-30/37mbar
Liquid gas G30 37 mbar (PL)
Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 59 x 918 x 546
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 - 502)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 13.8 KW

Accessories

- 1 x WOK attachment ring included