

REPAIR SPUR

REPAIR SPUR

Product Code: B8060011

THE BENEFITS

Manufactured from 2.5mm hot-dip galvanised cold-rolled steel, the newly designed FENCEMATE repair spur is the perfect solution for ground level cracks and breaks in 3" and 4" timber fence posts. A unique metal profile ensures the repair spur is strong, easy to install and designed to prevent further damage to timber posts.

Repair spur length:
1 metre

Slimline profile makes this easier to dig around and secure to the post

Flexes to absorb the load preventing any further damage from occurring

Varied hole spacing provides flexibility when fixing the repair spur

Unique metal profile provides maximum strength

FINISH

The FENCEMATE repair spur is finished with hot-dip galvanisation which provides high corrosion resistance.

INSTALLATION

Repair Spur: 3-Step Process

STEP 1

Dig a 500mm deep hole next to the fence post which needs support

STEP 2

Place the FENCEMATE repair spur in the hole and secure with suitable fixings

STEP 3

Secure the FENCEMATE repair spur with Post Concrete, ensuring the fence post is upright



RECOMMENDED SCREWS

M6 X 60 Ruspert Silver SITEMATE Counter-sunk Powerpro Timber Screw

70mm SITEMATE Wafer Head Timber Screws

70mm SITEMATE Hex Head Timber Screws

M8 x 150 SITEMATE Cup Square Hex Bolts and Nuts

M8 x 160 SITEMATE Roofing Bolts and Nuts

SITEMATE[®]
BY BIRKDALE



Scan here to watch the repair spur installation video



See our full FENCEMATE[®] range at: birkdalesales.com

T 0345 450 9000

F 0345 450 9085

E mail@birkdalesales.com