



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT GARDENIA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GHS product identifier : WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT GARDENIA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Waterborne coating for exterior use.

1.3. Details of the supplier of the safety data sheet

ICI Paints AkzoNobel,
Wexham Road,
Slough,
Berkshire,
SL2 5DS, U.K.
Tel.: +44 (0) 333 222 71 71
www.dulux.co.uk

e-mail address of person responsible for this SDS : dulux.advice@akzonobel.com

1.4 Emergency telephone number

Telephone number : Emergency Telephone : Slough +44 (0) 1753 550000

Version : 1

Date of previous issue : No previous validation

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



SECTION 2: Hazards identification

Signal word	: Warning
Hazard statements	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
<u>Precautionary statements</u>	
General	: P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	: P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. P264 - Wash hands thoroughly after handling.
Response	: P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Hazardous ingredients	: 1,2-Benzisothiazol-3(2h)-one OIT C(M)IT/MIT(3:1) methylisothiazolinone
Supplemental label elements	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
<u>Special packaging requirements</u>	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Acrylic Copolymer	-	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
bronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.055	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10)	[1]
diuron (ISO)	EC: 206-354-4 CAS: 330-54-1 Index: 006-015-00-9	≤0.04	Acute Tox. 4, H302 Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10)	[1] [2]
OIT	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	≤0.015	Aquatic Chronic 1, H410 (M=10) Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100)	[1]
pyrithione zinc	EC: 236-671-3 CAS: 13463-41-7	≤0.015	Aquatic Chronic 1, H410 (M=100) Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360 STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000)	[1]
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Aquatic Chronic 1, H410 (M=10) Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100)	[1]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤0.1	Aquatic Chronic 1, H410 (M=100) EUH071 Eye Irrit. 2, H319	[1] [2]
Methyl methacrylate	EC: 201-297-1 CAS: 80-62-6	≤0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	[1] [2]
m-xylene	EC: 203-576-3 CAS: 108-38-3	≤0.1	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
vinyl acetate	REACH #: 01-2119539477-28 EC: 203-545-4	≤0.1	Flam. Liq. 2, H225 Acute Tox. 4, H332 Carc. 2, H351	[1] [2]

SECTION 3: Composition/information on ingredients

n-butyl acrylate	CAS: 108-05-4 Index: 607-023-00-0 REACH #: 01-2119453155-43 EC: 205-480-7 CAS: 141-32-2	≤0.1	STOT SE 3, H335 Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 3, H412	[1] [2]
ethanediol	EC: 203-473-3 CAS: 107-21-1 Index: 603-027-00-1	≤0.1	Acute Tox. 4, H302	[1] [2]
2-ethoxyethanol	EC: 203-804-1 CAS: 110-80-5 Index: 603-012-00-X	<0.1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H331 Repr. 1B, H360FD	[1] [2]
2-methoxyethanol	EC: 203-713-7 CAS: 109-86-4 Index: 603-011-00-4	≤0.1	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Repr. 1B, H360FD See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, 2-octyl-2H-isothiazol-3-one, C(M)IT/MIT(3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
diuron (ISO)	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m ³ 8 hours.
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 ppm 8 hours. TWA: 67.5 mg/m ³ 8 hours. STEL: 15 ppm 15 minutes. STEL: 101.2 mg/m ³ 15 minutes.
Methyl methacrylate	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 416 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 208 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
m-xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes.
vinyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 35.2 mg/m ³ 15 minutes. TWA: 5 ppm 8 hours. TWA: 17.6 mg/m ³ 8 hours.

SECTION 8: Exposure controls/personal protection

n-butyl acrylate	STEL: 10 ppm 15 minutes. EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 26 mg/m ³ 15 minutes. STEL: 5 ppm 15 minutes. TWA: 5 mg/m ³ 8 hours. TWA: 1 ppm 8 hours.
ethanediol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 20 ppm 8 hours. Form: Vapor STEL: 40 ppm 15 minutes. Form: Vapor TWA: 52 mg/m ³ 8 hours. Form: Vapor STEL: 104 mg/m ³ 15 minutes. Form: Vapor
2-ethoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 2 ppm 8 hours. TWA: 8 mg/m ³ 8 hours.
2-methoxyethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. TWA: 1 ppm 8 hours. TWA: 3 mg/m ³ 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
bronopol (INN)	DNEL	Long term Oral	0.35 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	1.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	1.3 mg/m ³	General population	Local
	DNEL	Long term Inhalation	1.3 mg/m ³	General population	Local
	DNEL	Long term Dermal	1.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	3.7 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.1 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	4.2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	4.2 mg/m ³	Workers	Local
	DNEL	Long term	4.2 mg/m ³	Workers	Local

SECTION 8: Exposure controls/personal protection

diuron (ISO)	DNEL	Inhalation Short term	7 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Dermal	12.3 mg/m ³	Workers	Systemic	
	DNEL	Inhalation Long term	0.17 mg/m ³	Workers	Systemic	
	DNEL	Inhalation Long term	0.17 mg/m ³	Workers	Systemic	
pyrithione zinc	DNEL	Dermal Long term	5.79 mg/kg bw/day	Workers	Systemic	
	DNEL	Dermal Long term	0.01 mg/kg bw/day	Workers	Systemic	
2-(2-butoxyethoxy)ethanol	DNEL	Oral Long term	5 mg/kg bw/day	General population	Systemic	
	DNEL	Inhalation Long term	40.5 mg/m ³	General population	Local	
	DNEL	Inhalation Long term	40.5 mg/m ³	General population	Systemic	
	DNEL	Dermal Long term	50 mg/kg bw/day	General population	Systemic	
	DNEL	Inhalation Short term	60.7 mg/m ³	General population	Local	
	DNEL	Inhalation Long term	67.5 mg/m ³	Workers	Local	
	DNEL	Inhalation Long term	67.5 mg/m ³	Workers	Systemic	
	DNEL	Dermal Long term	83 mg/kg bw/day	Workers	Systemic	
	DNEL	Inhalation Short term	101.2 mg/m ³	Workers	Local	
	Methyl methacrylate	DNEL	Dermal Long term	8.2 mg/kg bw/day	General population	Systemic
		DNEL	Dermal Long term	13.67 mg/kg bw/day	Workers	Systemic
		DNEL	Inhalation Long term	74.3 mg/m ³	General population	Systemic
DNEL		Inhalation Long term	104 mg/m ³	General population	Local	
DNEL		Inhalation Long term	208 mg/m ³	Workers	Local	
DNEL		Inhalation Long term	208 mg/m ³	Workers	Systemic	
m-xylene	DNEL	Oral Long term	12.5 mg/kg bw/day	General population	Systemic	
	DNEL	Inhalation Long term	65.3 mg/m ³	General population	Local	
	DNEL	Inhalation Long term	65.3 mg/m ³	General population	Systemic	
	DNEL	Dermal Long term	125 mg/kg bw/day	General population	Systemic	
	DNEL	Dermal Long term	212 mg/kg bw/day	Workers	Systemic	
	DNEL	Inhalation Long term	221 mg/m ³	Workers	Local	
	DNEL	Inhalation Long term	221 mg/m ³	Workers	Systemic	
	DNEL	Inhalation Short term	260 mg/m ³	General population	Local	
	DNEL	Inhalation Short term	260 mg/m ³	General population	Systemic	
	DNEL	Inhalation Short term	442 mg/m ³	Workers	Local	
DNEL	Inhalation Short term	442 mg/m ³	Workers	Systemic		

SECTION 8: Exposure controls/personal protection

vinyl acetate	DNEL	Long term Dermal	0.42 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	17.6 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	17.6 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	35.2 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	35.2 mg/m ³	Workers	Systemic
n-butyl acrylate	DNEL	Long term Inhalation	11 mg/m ³	Workers	Local
ethanediol	DNEL	Long term Inhalation	7 mg/m ³	General population	Local
	DNEL	Long term Inhalation	35 mg/m ³	Workers	Local
	DNEL	Long term Dermal	53 mg/kg bw/day	General population	Systemic
2-ethoxyethanol	DNEL	Long term Dermal	106 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	83 µg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic
2-methoxyethanol	DNEL	Long term Oral	0.55 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.91 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.2 mg/m ³	Workers	Systemic

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

SECTION 8: Exposure controls/personal protection

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid.
- Color** : White.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 8 [Conc. (% w/w): 100%]
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : 100°C
- Flash point** : Closed cup: 999°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Upper/lower flammability or explosive limits** : Not available.
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Relative density** : 1.22
- Solubility(ies)** : Easily soluble in the following materials: cold water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.

SECTION 9: Physical and chemical properties

Viscosity : Kinematic (room temperature): 5.75 cm²/s

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
m-xylene	LD50 Dermal	Rabbit	14100 uL/kg	-
	LD50 Intraperitoneal	Mouse	2003 uL/kg	-
	LD50 Oral	Rat	4988 mg/kg	-
	LDLo Intraperitoneal	Mammal - species unspecified	2 g/kg	-
	LDLo Subcutaneous	Mammal - species unspecified	5 g/kg	-
n-butyl acrylate	TDL0 Dermal	Rat	0.92 mL/kg	-
	TDL0 Dermal	Rat	8 mg/kg	-
	LC50 Inhalation Gas.	Rat	2730 ppm	4 hours
ethanediol	LD50 Oral	Rat	900 mg/kg	-
	LD50 Intraperitoneal	Rat	5010 mg/kg	-
	LD50 Intravenous	Rat	3260 mg/kg	-
	LD50 Oral	Rat	4700 mg/kg	-
2-ethoxyethanol	LD50 Route of exposure unreported	Rat	13 g/kg	-
	LD50 Subcutaneous	Rat	2800 mg/kg	-
	LD50 Dermal	Rabbit	3.6 g/kg	-
	LD50 Dermal	Rat	3900 mg/kg	-
	LD50 Intraperitoneal	Mouse	1710 mg/kg	-
	LD50 Intraperitoneal	Mouse	1707 mg/kg	-
	LD50 Intraperitoneal	Rat	2800 mg/kg	-
	LD50 Intravenous	Mouse	3900 mg/kg	-
	LD50 Intravenous	Rabbit	900 mg/kg	-
	LD50 Intravenous	Rat	2400 mg/kg	-
	LD50 Oral	Guinea pig	1.4 g/kg	-
	LD50 Oral	Guinea pig	1400 mg/kg	-
	LD50 Oral	Guinea pig	950 mg/kg	-
	LD50 Oral	Mouse	4000 mg/kg	-
	LD50 Oral	Mouse	2451 mg/kg	-
LD50 Oral	Mouse	2451 mg/kg	-	
LD50 Oral	Rabbit	1275 mg/kg	-	
LD50 Oral	Rabbit	1275 mg/kg	-	

SECTION 11: Toxicological information

2-methoxyethanol	LD50 Oral	Rat	3 g/kg	-
	LD50 Oral	Rat	2125 mg/kg	-
	LD50 Oral	Rat	3527 mg/kg	-
	LD50 Oral	Rat	8103 mg/kg	-
	LD50 Oral	Rat	2460 mg/kg	-
	LD50 Oral	Rat	2125 mg/kg	-
	LD50 Route of exposure unreported	Guinea pig	3070 mg/kg	-
	LD50 Route of exposure unreported	Mouse	5799 mg/kg	-
	LD50 Route of exposure unreported	Rat	7750 mg/kg	-
	LD50 Subcutaneous	Rabbit	2 g/kg	-
	LD50 Subcutaneous	Rat	3400 mg/kg	-
	LDLo Oral	Human	143 mg/kg	-
	LDLo Subcutaneous	Mouse	5 g/kg	-
	TDLo Oral	Rat	1000 mg/kg	-
	TDLo Oral	Woman - Female	0.8 mL/kg	-
	LD50 Dermal	Rabbit	1280 mg/kg	-
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Intraperitoneal	Mouse	2147 mg/kg	-
	LD50 Intraperitoneal	Rat	2500 mg/kg	-
	LD50 Intravenous	Rat	2068 mg/kg	-
	LD50 Oral	Guinea pig	950 mg/kg	-
	LD50 Oral	Mouse	2560 mg/kg	-
	LD50 Oral	Mouse	2800 mg/kg	-
	LD50 Oral	Rabbit	890 mg/kg	-
	LD50 Oral	Rabbit	890 mg/kg	-
	LD50 Oral	Rat	2370 mg/kg	-
	LD50 Oral	Rat	2460 mg/kg	-
	LDLo Oral	Human	3380 mg/kg	-
	LDLo Oral	Human	143 mg/kg	-
	TDLo Intraperitoneal	Rat	50 mg/kg	-
	TDLo Intraperitoneal	Rat	150 mg/kg	-
	TDLo Oral	Guinea pig	200 mg/kg	-
	TDLo Oral	Guinea pig	300 mg/kg	-
	TDLo Oral	Rat	250 mg/kg	-
	TDLo Oral	Rat	200 mg/kg	-
	TDLo Oral	Rat	150 mg/kg	-
TDLo Oral	Rat	200 mg/kg	-	
TDLo Oral	Rat	2000 mg/kg	-	
TDLo Oral	Rat	50 mg/kg	-	

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bronopol (INN)	Skin - Moderate irritant	Human	-	10 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
OIT C(M)IT/MIT(3:1) 2-(2-butoxyethoxy)ethanol	Skin - Moderate irritant	Rabbit	-	80 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Human	-	0.01 %	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
m-xylene	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
n-butyl acrylate	Skin - Severe irritant	Rabbit	-	24 hours 10 ug	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-

SECTION 11: Toxicological information

ethanediol	Eyes - Mild irritant	Rabbit	-	mg	-
	Skin - Mild irritant	Rabbit	-	50 mg	-
				24 hours 10	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Eyes - Mild irritant	Rabbit	-	1 hours 100	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440	-
2-ethoxyethanol	Skin - Mild irritant	Rabbit	-	555 mg	-
	Eyes - Mild irritant	Guinea pig	-	10 ug	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Eyes - Moderate irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
2-methoxyethanol	Eyes - Mild irritant	Guinea pig	-	10 ug	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	24 hours 483	-
				mg	

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
diuron (ISO)	Category 2	-	-
pyrithione zinc	Category 1	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

SECTION 11: Toxicological information**Symptoms related to the physical, chemical and toxicological characteristics**

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information**12.1 Toxicity**

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
bronopol (INN)	Acute EC50 0.02 ppm Fresh water	Algae - Desmodesmus subspicatus	96 hours
diuron (ISO)	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 11.17 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days
	Acute EC50 0.0023 mg/l Fresh water	Algae - Chlorella pyrenoidosa	96 hours
	Acute EC50 2.4 ppb Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.005 mg/l Fresh water	Aquatic plants - Lemna sp.	96 hours
	Acute EC50 7.6 µg/l Fresh water	Aquatic plants - Lemna aequinoctialis	72 hours
	Acute EC50 7.2 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

SECTION 12: Ecological information

	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 8.4 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 2.41 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 5.89 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 2.47 µg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Acute LC50 3044 µg/l Marine water	Crustaceans - Palaemon serratus - Zoea	48 hours
	Acute LC50 1.95 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 3100 µg/l Fresh water	Fish - Morone saxatilis	96 hours
	Acute LC50 2900 µg/l Fresh water	Fish - Cyprinus carpio - Fry	96 hours
	Chronic EC10 0.11 µg/l Fresh water	Algae - Fragilaria capucina - Exponential growth phase	96 hours
	Chronic EC10 0.76 µg/l Fresh water	Algae - Fragilaria capucina ssp. rumpens	96 hours
	Chronic IC10 0.47 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.7 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.49 µg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 0.283 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.34 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic NOEC 0.34 µg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 33.4 µg/l Fresh water	Fish - Pimephales promelas - Embryo	63 days
OIT	Acute EC10 0.000224 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.084 mg/l	Algae - Desmodesmus subspicatus	72 hours
	Acute EC50 0.00129 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.42 mg/l	Daphnia	48 hours
	Acute EC50 107 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 47 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 8.5 ppb	Fish - Pimephales promelas	35 days
pyrithione zinc	Acute EC50 0.51 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Acute EC50 8.25 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 0.36 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
m-xylene	Chronic NOEC 2.7 ppb Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 4900 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 8.54 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 7.09 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 5.77 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 5 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 3.53 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8.84 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 8.52 mg/l Marine water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute LC50 55.7 mg/l Fresh water	Daphnia - Daphnia magna -	48 hours

SECTION 12: Ecological information

vinyl acetate	Acute LC50 23.6 mg/l Fresh water	Neonate Daphnia - Daphnia magna - Neonate	48 hours	
	Acute LC50 16000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 12900 µg/l Fresh water	Fish - Poecilia reticulata	96 hours	
	Acute LC50 8400 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
	Acute LC50 9.2 ul/L Marine water	Fish - Morone saxatilis - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
	Acute LC50 18 mg/l	Fish - Lepomis macrochirus	96 hours	
	Acute LC50 19 mg/l	Fish - Pimephales promelas	96 hours	
	ethanediol	Acute LC50 13140000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
		Acute LC50 13900000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 10500000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 6900000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 10000000 µg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 41000 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
		Acute LC50 41100000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
		Acute LC50 47400000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 46300000 µg/l Fresh water		Daphnia - Daphnia magna - Neonate	48 hours	
Acute LC50 45500000 µg/l Fresh water		Daphnia - Daphnia magna - Neonate	48 hours	
2-ethoxyethanol	Acute LC50 27540 mg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
	Acute LC50 52500 mg/l Fresh water	Fish - Pimephales promelas - Fry	96 hours	
	Acute LC50 43900 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
	Acute LC50 49000000 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours	
	Acute LC50 8050000 µg/l Fresh water	Fish - Pimephales promelas	96 hours	
	Acute LC50 >10000000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours	
	Acute LC50 >10000000 µg/l Marine water	Fish - Menidia beryllina	96 hours	
	2-methoxyethanol	Acute LC50 >100 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
		Acute LC50 >10000000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
		Acute LC50 >10000000 µg/l Marine water	Fish - Menidia beryllina	96 hours
Acute LC50 >100 ppm Fresh water		Fish - Oncorhynchus mykiss	96 hours	

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
bronopol (INN)	0.18	-	low
diuron (ISO)	2.84	5.2	low
OIT	2.45	-	low
pyrithione zinc	0.9	11	low
2-(2-butoxyethoxy)ethanol	1	-	low
Methyl methacrylate	1.38	-	low
m-xylene	3.2	8.1 to 25.9	low
vinyl acetate	0.73	3.16	low
n-butyl acrylate	2.38	17.27	low
ethanediol	-1.36	-	low
2-ethoxyethanol	-0.32	-	low
2-methoxyethanol	-0.77	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

Additional information

IMDG : **Emergency schedules** Not applicable.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorization****Annex XIV**

None of the components are listed, or the component present is below its threshold.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
2-ethoxyethanol	Toxic to reproduction	Recommended	ED/01/2018	10/1/2019
2-methoxyethanol	Toxic to reproduction	Recommended	ED/01/2018	10/1/2019

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

SECTION 15: Regulatory information

VOC for Ready-for-Use Mixture : Not applicable.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)


Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Other information

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	TOXIC TO REPRODUCTION - Category 1B
Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 19 September 2022

SECTION 16: Other information

Date of issue/ Date of revision : 19 September 2022

Date of previous issue : No previous validation

Version : 1

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands