



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GHS product identifier : WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Waterborne coating for exterior use.

1.3. Details of the supplier of the safety data sheet

ICI Paints AkzoNobel,
Wexham Road,
Slough,
Berkshire,
SL2 5DS, U.K.
Tel.: +44 (0) 333 222 71 71
www.dulux.co.uk

e-mail address of person responsible for this SDS : dulux.advice@akzonobel.com

1.4 Emergency telephone number

Telephone number : Emergency Telephone : Slough +44 (0) 1753 550000

Version : 20

Date of previous issue : 19-9-2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317
Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 2: Hazards identification

| | |
|---|---|
| Hazard statements | : H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects. |
| Precautionary statements | |
| General | : P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand. |
| Prevention | : P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapour. |
| Response | : P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. |
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations. |
| Hazardous ingredients | : OIT 1,2-benzisothiazol-3(2H)-one C(M)IT/MIT(3:1) methylisothiazolinone |
| Supplemental label elements | : Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : |
| Special packaging requirements | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|-------------------------|--|------|---|---|------|
| bronopol (INN) | EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8 | ≤0.1 | Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 | ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10 | [1] |
| diuron (ISO) | EC: 206-354-4 | ≤0.1 | Acute Tox. 4, H302 | ATE [Oral] = 500 | [1] |

Date of issue/Date of revision : 14-12-2022 Date of previous issue : 19-9-2022 Version : 20 2/20

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 3: Composition/information on ingredients

| | | | | | |
|------------------------------|--|------|--|--|-----|
| OIT | CAS: 330-54-1 Index: 006-015-00-9 | | Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | mg/kg M [Acute] = 10 M [Chronic] = 10 | |
| pyrithione zinc | EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5 | ≤0.1 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | [1] |
| 1,2-benzisothiazol-3(2H)-one | EC: 236-671-3 CAS: 13463-41-7 | ≤0.1 | Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 100 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l M [Acute] = 1000 M [Chronic] = 10 | [1] |
| C(M)IT/MIT(3:1) | EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 | ≤0.1 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 | ATE [Oral] = 500 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1 | [1] |
| methylisothiazolinone | REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5 | ≤0.1 | Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Skin Irrit. 2, H315: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | [1] |
| | EC: 220-239-6 CAS: 2682-20-4 Index: self classification | ≤0.1 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10 M [Chronic] = 1 | [1] |

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|--|--|---|--|--|
| | | | See Section 16 for the full text of the H statements declared above. | | |
|--|--|--|---|--|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

SECTION 4: First aid measures

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1), 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Over-exposure signs/symptoms

| | |
|---------------------|--|
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |

4.3 Indication of any immediate medical attention and special treatment needed

| | |
|----------------------------|---|
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |

SECTION 5: Firefighting measures

5.1 Extinguishing media

| | |
|---------------------------------------|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |

5.2 Special hazards arising from the substance or mixture

| | |
|--|---|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |

5.3 Advice for firefighters

| | |
|---|---|
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|--|
| diuron (ISO) | EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m ³ 8 hours. |

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|-----------------------|--------------------------|--------------------|----------|
| bronopol (INN) | DNEL | Short term Dermal | 0.004 mg/cm ² | General population | Local |
| | DNEL | Long term Dermal | 0.004 mg/cm ² | General population | Local |
| | DNEL | Short term Dermal | 0.008 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 0.008 mg/cm ² | Workers | Local |
| | DNEL | Long term Oral | 0.18 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Oral | 0.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 0.6 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 0.6 mg/m ³ | General population | Systemic |
| | DNEL | Long term Dermal | 0.7 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term | 1.8 mg/m ³ | General | Systemic |

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 8: Exposure controls/personal protection

| | | | | | |
|------------------------------|-----------------|--------------------------------|-----------------------------|-----------------------|----------|
| diuron (ISO) | DNEL | Inhalation Long term Dermal | 2 mg/kg bw/day | population Workers | Systemic |
| | DNEL | Short term Dermal | 2.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 2.5 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 2.5 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 3.5 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Dermal | 6 mg/kg bw/day | Workers | Systemic |
| | DNEL | Short term Inhalation | 10.5 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.17 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 5.79 mg/ kg bw/day | Workers | Systemic |
| | pyrithione zinc | DNEL | Long term Dermal | 0.01 mg/ kg bw/day | Workers |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal | 0.345 mg/ kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.966 mg/ kg bw/day | Workers | Systemic |
| C(M)IT/MIT(3:1) | DNEL | Long term Inhalation | 1.2 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 6.81 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.02 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 0.02 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m ³ | Workers | Local |
| | DNEL | Long term Oral | 0.09 mg/ kg bw/day | General population | Systemic |
| | DNEL | Short term Oral | 0.11 mg/ kg bw/day | General population | Systemic |
| methylisothiazolinone | DNEL | Long term Inhalation | 0.021 mg/ m ³ | General population | Local |
| | DNEL | Long term Inhalation | 0.021 mg/ m ³ | Workers | Local |
| | DNEL | Long term Oral | 0.027 mg/ kg bw/day | General population | Systemic |
| | DNEL | Short term Inhalation | 0.043 mg/ m ³ | General population | Local |
| | DNEL | Short term Inhalation | 0.043 mg/ m ³ | Workers | Local |
| | DNEL | Short term Oral | 0.053 mg/ kg bw/day | General population | Systemic |

PNECs

No PNECs available

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

| | |
|--|---|
| Physical state | : Liquid. |
| Colour | : White. |
| Odour | : Not available. |
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : 100°C (212°F) |
| Flammability | : Not available. |
| Lower and upper explosion limit | : Not available. |
| Flash point | : Closed cup: 999°C (1830.2°F) [Pensky-Martens] |
| Auto-ignition temperature | : |

| Ingredient name | °C | °F | Method |
|---|------|-------|-----------|
| 2-(2-butoxyethoxy)ethanol | 210 | 410 | DIN 51794 |
| 2-ethylhexyl acrylate | 252 | 485.6 | |
| n-butyl acrylate | 275 | 527 | |
| 2-(2-butoxyethoxy)ethyl acetate | 290 | 554 | |
| Cellulose, 2-hydroxyethyl ether | 380 | 716 | |
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | 393 | 739.4 | |
| Methyl methacrylate | 400 | 752 | DIN 51794 |
| diuron (ISO) | 401 | 753.8 | EU A.16 |
| vinyl acetate | 402 | 755.6 | |
| sodium acrylate | 438 | 820.4 | |
| ethanol | 455 | 851 | DIN 51794 |
| acetic acid | 463 | 865.4 | |
| styrene | 490 | 914 | |
| p-toluenesulphonic acid, containing a maximum of 5 % H ₂ SO ₄ | >465 | >869 | EU A.15 |
| m-xylene | 527 | 980.6 | |

| | |
|----------------------------------|---|
| Decomposition temperature | : Not available. |
| pH | : 8 [Conc. (% w/w): 100%] [DIN EN 1262] |
| Viscosity | : Kinematic: 555 mm ² /s [DIN EN ISO 3219] |
| Solubility(ies) | : |

| Media | Result |
|------------|--------------------------------|
| cold water | Easily soluble [OESO (TG 105)] |

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 9: Physical and chemical properties

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|--|-------------------------|---------------|-------------|-------------------------|------------|----------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| ammonia | 360.03 | 48 | | | | |
| vinyl acetate | 84.76 | 11.3 | | | | |
| ethanol | 42.95 | 5.7 | | | | |
| Methyl methacrylate | 27.75 | 3.7 | | | | |
| water | 23.8 | 3.2 | | | | |
| acetic acid | 15.59 | 2.1 | | | | |
| styrene | 6.4 | 0.85 | | | | |
| m-xylene | 6 | 0.8 | | | | |
| n-butyl acrylate | 3.75 | 0.5 | | | | |
| 2-ethylhexyl acrylate | 0.18 | 0.024 | | | | |
| Distillates (petroleum), solvent-refined heavy paraffinic | <0.08 | <0.011 | ASTM D 5191 | | | |
| Distillates (petroleum), hydrotreated heavy paraffinic | <0.08 | <0.011 | ASTM D 5191 | | | |
| 2-(2-butoxyethoxy)ethanol | 0.022 | 0.0029 | | | | |
| 1-isopropyl-2,2-dimethyltrimethylene diisobutyrate | <0.011 | <0.0015 | EU A.4 | | | |
| isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol | 0.0098 | 0.0013 | EU A.4 | | | |
| Poly(oxy-1,2-ethanediyl), α -hydro- ω -hydroxy- Ethane-1,2-diol, ethoxylated | 0.0000003 | 0.00000004 | | | | |
| pyrithione zinc | <0.000000008 | <0.0000000011 | OECD 104 | | | |
| diuron (ISO) | 0.000000006 | 0.0000000008 | OECD 104 | 0.0000013 | 0.00000017 | OECD 104 |
| propylidynetrimethanol | 0 | 0 | | | | |
| bronopol (INN) | 0 | 0 | | 0 | 0 | |
| C(M)IT/MIT(3:1) | 0 | 0 | | | | |
| 2-(2-butoxyethoxy)ethyl acetate | 0 | 0 | | | | |

Density : 1.263 g/cm³ [DIN EN ISO 2811-1]

Vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 10: Stability and reactivity

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|------------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| bronopol (INN) | 500 | 1100 | N/A | N/A | N/A |
| diuron | 500 | N/A | N/A | N/A | N/A |
| 2-octyl-2H-isothiazol-3-one | 100 | 300 | N/A | N/A | 0.05 |
| pyrithione zinc | 100 | N/A | N/A | N/A | 0.05 |
| 1,2-benzisothiazol-3(2H)-one | 500 | N/A | N/A | N/A | N/A |
| C(M)IT/MIT(3:1) | 100 | 50 | N/A | N/A | 0.05 |
| 2-methyl-2H-isothiazol-3-one | 100 | 300 | N/A | 0.5 | N/A |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|-----------------|-------------|
| bronopol (INN) | Skin - Mild irritant | Rabbit | - | 24 hours 500 mg | - |
| OIT 1,2-benzisothiazol-3(2H)-one C(M)IT/MIT(3:1) | Skin - Moderate irritant | Human | - | 10 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 80 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 100 mg | - |
| | Skin - Mild irritant | Human | - | 48 hours 5 % | - |
| | Skin - Severe irritant | Human | - | 0.01 % | - |

Conclusion/Summary : Not available.

Sensitisation

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| bronopol (INN) | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 11: Toxicological information

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| diuron (ISO) | Category 2 | - | - |
| pyrithione zinc | Category 1 | - | - |

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name | Result | Species | Exposure |
|--------------------------------------|-------------------------------------|--|----------|
| bronopol (INN) | Acute EC50 0.02 ppm Fresh water | Algae - Desmodesmus subspicatus | 96 hours |
| | Acute EC50 1.6 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| diuron (ISO) | Acute LC50 11.17 ppm Fresh water | Fish - Lepomis macrochirus | 96 hours |
| | Chronic NOEC 1.94 ppm | Fish - Oncorhynchus mykiss | 49 days |
| | Acute EC50 0.0023 mg/l Fresh water | Algae - Chlorella pyrenoidosa | 96 hours |
| | Acute EC50 0.0027 mg/l Fresh water | Algae - Scenedesmus quadricauda | 96 hours |
| | Acute EC50 7.6 µg/l Fresh water | Aquatic plants - Lemna aequinoctialis | 72 hours |
| | Acute EC50 0.005 mg/l Fresh water | Aquatic plants - Lemna sp. | 96 hours |
| | Acute EC50 7.2 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute EC50 8.6 mg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 8.6 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute EC50 8.4 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute IC50 2.41 µg/l Marine water | Aquatic plants - Halodule uninervis | 72 hours |
| | Acute IC50 5.89 µg/l Marine water | Aquatic plants - Halodule uninervis | 72 hours |
| | Acute IC50 2.47 µg/l Marine water | Aquatic plants - Zostera muelleri | 72 hours |
| | Acute LC50 3044 µg/l Marine water | Crustaceans - Palaemon serratus - Zoea | 48 hours |
| | Acute LC50 2900 µg/l Fresh water | Fish - Cyprinus carpio - Fry | 96 hours |
| | Acute LC50 3100 µg/l Fresh water | Fish - Morone saxatilis | 96 hours |
| | Acute LC50 1.95 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Chronic EC10 0.76 µg/l Fresh water | Algae - Fragilaria capucina ssp. rumpens | 96 hours |
| | Chronic EC10 0.11 µg/l Fresh water | Algae - Fragilaria capucina - Exponential growth phase | 96 hours |
| | Chronic IC10 0.47 µg/l Marine water | Aquatic plants - Halodule uninervis | 72 hours |
| Chronic IC10 0.7 µg/l Marine water | Aquatic plants - Halodule uninervis | 72 hours | |
| Chronic IC10 0.49 µg/l Marine water | Aquatic plants - Zostera muelleri | 72 hours | |
| Chronic NOEC 0.283 µg/l Marine water | Algae - Nitzschia pungens | 96 hours | |
| Chronic NOEC 0.34 µg/l Marine water | Aquatic plants - Halodule uninervis | 72 hours | |
| Chronic NOEC 0.34 µg/l Marine water | Aquatic plants - Zostera muelleri | 72 hours | |
| Chronic NOEC 26.4 ppb | Fish - Pimephales promelas | 60 days | |
| Chronic NOEC 26.4 ppb | Fish - Pimephales promelas | 60 days | |
| Chronic NOEC 26.4 ppb | Fish - Pimephales promelas | 60 days | |
| Chronic NOEC 33.4 µg/l Fresh water | Fish - Pimephales promelas - Embryo | 63 days | |
| OIT | Acute EC10 0.000224 mg/l | Algae - Navicula peliculosa | 48 hours |
| | Acute EC50 0.084 mg/l | Algae - Desmodesmus subspicatus | 72 hours |
| | Acute EC50 0.00129 mg/l | Algae - Navicula peliculosa | 48 hours |
| | Acute EC50 0.42 mg/l | Daphnia | 48 hours |
| | Acute EC50 107 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 47 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

SECTION 12: Ecological information

| | | | |
|------------------------------|--|--|--|
| pyrithione zinc | Chronic NOEC 74 ppb Fresh water Chronic NOEC 8.5 ppb Acute EC50 0.51 µg/l Marine water | Daphnia - Daphnia magna Fish - Pimephales promelas Algae - Thalassiosira pseudonana | 21 days 35 days 96 hours |
| | Acute EC50 8.25 ppb Fresh water Acute LC50 2.68 ppb Fresh water Chronic EC10 0.36 µg/l Marine water | Daphnia - Daphnia magna Fish - Pimephales promelas Algae - Thalassiosira pseudonana | 48 hours 96 hours 96 hours |
| 1,2-benzisothiazol-3(2H)-one | Chronic NOEC 2.7 ppb Fresh water Acute EC50 1.5 mg/l Acute EC50 0.4 mg/l Acute IC50 0.067 mg/l | Daphnia - Daphnia magna Daphnia - Daphnia magna Daphnia - Pseudomonas putia Algae - Pseudokirchneriella subcapitata | 21 days 48 hours 16 hours 72 hours |
| methylisothiazolinone | Acute LC50 1.3 mg/l Acute EC50 0.24 mg/l Acute EC50 0.18 ppm Fresh water Acute LC50 0.18 mg/l Acute LC50 12.4 mg/l Acute LC50 6 mg/l Acute LC50 0.07 ppm Fresh water | Fish - Ochorhynchus mykiss Daphnia Daphnia - Daphnia magna Fish Fish - Lepomis Macrochirus Fish - Oncorhynchus Mykiss Fish - Oncorhynchus mykiss | 96 hours 48 hours 48 hours 96 hours 96 hours 96 hours 96 hours |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| bronopol (INN) | 0.18 | - | low |
| diuron (ISO) | 2.84 | 5.2 | low |
| OIT | 2.45 | - | low |
| pyrithione zinc | 0.9 | 11 | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation |
|--------------|--|
| EWC 08 01 12 | waste paint and varnish other than those mentioned in 08 01 11 |

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA |
|--|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - |
| 14.4 Packing group | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. |

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878



SECTION 14: Transport information

Additional information

IMDG : Emergency schedules Not applicable.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 15: Regulatory information

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Eurasian Economic Union :

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| Skin Sens. 1, H317 | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements

| | |
|------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H290 | May be corrosive to metals. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |

WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT

SECTION 16: Other information

| | |
|--------|--|
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H360 | May damage fertility or the unborn child. |
| H361d | Suspected of damaging the unborn child. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

| | |
|-------------------|---|
| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Carc. 2 | CARCINOGENICITY - Category 2 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Met. Corr. 1 | CORROSIVE TO METALS - Category 1 |
| Repr. 1B | REPRODUCTIVE TOXICITY - Category 1B |
| Repr. 2 | REPRODUCTIVE TOXICITY - Category 2 |
| Skin Corr. 1 | SKIN CORROSION/IRRITATION - Category 1 |
| Skin Corr. 1A | SKIN CORROSION/IRRITATION - Category 1A |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Corr. 1C | SKIN CORROSION/IRRITATION - Category 1C |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| Skin Sens. 1B | SKIN SENSITISATION - Category 1B |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

Date of printing : 14 December 2022
Date of issue/ Date of revision : 14 December 2022
Date of previous issue : 19 September 2022
Version : 20

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

 **WEATHERSHIELD ALL WEATHER PROTECTION SMOOTH MASONRY PAINT**

SECTION 16: Other information

or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands