

SEAL IT BLEED BLOCKER

Primer For Use On Bitumen Roofs Prior To Use Of Seal It Liquid Membrane

Technical Data Sheet



SEAL IT ROOF SEAL RANGE

Description:

A one part solvent-free primer for preparation of bitumen surfaces and roofing felt prior to the application of SEAL IT LIQUID MEMBRANE or EASISEAL PRO Weatherproofing Compound.

Features & Benefits:

- ◆ Enhances the bond strength of Seal It ROOF SEAL Membrane and EASISEAL PRO to bitumen based substrates, asphalt and felt substrates.
- ◆ Quick and easy to use.
- ◆ Blocks surface staining from bitumen coatings.

Preparation

Surfaces to be primed should be free from dirt, oil, grease, dust or loosely bound coatings or any other contaminants that may affect adhesion. Organic growth should be removed and treated with Bond It MOULD STOP. Surfaces MUST be dry prior to application.



Application

Temperature during application of primer **must be** above +5°C. The primer is coloured light blue to identify treated areas. Stir BLEED BLOCKER before use to ensure all pigment and polymer is fully dispersed. Apply a single coat of SEAL IT BLEED BLOCKER to the surface with a brush or roller. Follow coverage rate to ensure minimum thickness is achieved. Leave to fully cure, normally overnight, in cold weather it may require 48 hours to fully cure. Product will dry to a light blue film. If a second coat is required, this should only be applied after first coat has **fully** cured.

It is essential that bituminous materials are completely covered with SEAL IT BLEED BLOCKER prior to application of SEAL IT LIQUID MEMBRANE. Particular care must be given to rough surfaces such as bitumen felt, where any gaps in primer coverage can lead to product failure. It is essential that any bitumen based surfaces are covered with at least 2 coats of primer of the SEAL IT LIQUID MEMBRANE System will **FAIL**. Seams and edges may even require a third coat as bitumen can be more exposed in these sections. Alternatively, SEAL IT CRACKS AND EDGING SEALER can be used. Please consult separate TDS for this product.



Continue with the application of SEAL IT LIQUID MEMBRANE or EASISEAL PRO as per the Technical Datasheet/package details. It is recommended that SEAL IT REINFORCING MAT is bedded into the SEAL IT LIQUID MEMBRANE coating to extend the lifespan of the product over bitumen substrates.



We recommend a small discreet area approximately 1m² is treated with the SEAL IT LIQUID MEMBRANE prior to applying to the full surface area for the purpose of identifying any adverse reaction between product and the substrate.

Any of the available colours of SEAL IT LIQUID MEMBRANE or EASISEAL PRO can be used following the correct application of this primer, but discolouration may occur where primer coverage is incomplete or with waterbased bitumen coatings..

Cleaning

Clean brushes or rollers with soap and water before the material has a chance to harden.

Coverage

1 litre of SEAL IT OCRS BLEED BLOCKER is sufficient to cover approximately 3m² (1 coat) or 1.5m² (if applying 2 coats). Therefore, 12.5L approx: 60m² or 30m² if applying 2 coats.

Size

2.5L and 12.5L metal tins.

Colour

Light blue and dries pale blue to identify coated areas.

Shelf Life

36 months from date of manufacture when stored in sealed tins.

Storage Conditions

Store in cool, dry conditions between +5°C and +25°C. Protect from frost and direct sunlight.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user’s responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Cure Speed @+18°C	18 hours
Application Temperature	+5 to +25°C
Density	ca.1.25 g/cm³
Solids Content	Approx. 60%
Commodity Code	2715000000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BDOCRSP2	Light Blue	2.5L	5056437401151	Q330-30HV-U00G-7GAP
BDOCRSP12	Light Blue	12.5L	5056437401373*	Q330-30HV-U00G-7GAP

* Available to special request



Part of the Seal It One Coat Roof Seal Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson’s Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 6: Updated 22/07/25
Supersedes: V6 29/03/23

