

bond it

Never compromise on quality!

SEAL IT ROOF SEAL REINFORCING MAT

Spunbond Polyester Repair And Strengthening Material

Technical Data Sheet



SEAL IT ONE COAT ROOF SEAL RANGE

Description:

A heavy duty, spunbond polyester mat which is tear and puncture resistant. For use with SEAL IT LIQUID MEMBRANE system.

Benefits:

- ◆ Used in conjunction with SEAL IT LIQUID MEMBRANE.
- ◆ Heavy duty spunbond polyester.
- ◆ Tear and puncture resistant.
- ◆ Improves strength.
- ◆ Rapid repair for blisters, splits and tears in existing substrates prior to coating.

Uses

Use of the **SEAL IT REINFORCING MAT** with SEAL IT LIQUID MEMBRANE provides more than 50% strength improvement when product has cured. It can also be used to make good tears, rips and damage to substrates as a repair patch, prior to using SEAL IT LIQUID MEMBRANE.

Preparation

Follow surface preparation instructions for SEAL IT LIQUID MEMBRANE. **SEAL IT REINFORCING MAT** can be applied straight off the roll or cut to size prior to use.

Application

Apply a 1mm coat of SEAL IT LIQUID MEMBRANE. and press the reinforcement mat into it with light pressure whilst the coating is still wet (refer to separate instructions for use of SEAL IT LIQUID MEMBRANE). A minimum overlap of 5cm is recommended between adjoining strips of **SEAL IT REINFORCING MAT**. Use a small amount of SEAL IT LIQUID MEMBRANE to adhere the overlapping region. When the first coat has dried sufficiently to walk on (approximately 8 hours depending on conditions) apply a second layer of SEAL IT LIQUID MEMBRANE to fully cover the mat and bring total thickness to at least 2mm.

When using as a patch repair over blisters, splits, etc. then the mat and coating must extend at least 5cm beyond the affected area.

Size

1M x 25M roll.

Colour

White.

Storage Conditions

Shelf life is indefinite for the mat when kept in original packaging in cool, dry conditions.

Disposal of Packaging

Do not leave empty packaging where it could be harmful to children, animals or the environment. Dispose of empty packaging to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.



Specification Summary

Colour	White
Composition	Spunbond polyester
Weight	70gsm
Size	25M length; 1.016M width

Product / Order Details:

Code	Colour	Size	Barcode
BDOCRSM25	White	1M x 25M	5056437401168



Part of the Seal It One Coat Roof Seal Range



The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



Rev: V2 05/08/20
 Supercedes: V1 01/01/20