



UniBase Bronze

Underlay

100%
recyclable PE
foam wood
underlay
offering
terrific value

Suitable for use with laminate
and engineered wood flooring
(floating floor installation).

- Longer-lasting flooring**
 UniBase gives your floor covering the perfect level of support to protect it from excess wear and even high impact damage - all of which helps your floor look good for longer!
- Lightening the load**
 The ultra lightweight polyethylene foam material makes UniBase so easy to lift and manoeuvre... you won't believe just how much time and effort that can save you on every installation.
- Protects against damp**
 Don't worry about moisture rising up from the sub-floor - UniBase Silver and UniBase Gold have the added benefit of a metallised vapour barrier that overlaps and protects your floor covering and keeps your room dry as a bone.
- Kinder to the environment**
 100% recyclable closed cell polyethylene foam means that when you use UniBase, you're being kinder to the environment in the long run.

Technical Data

Properties	Unit	Value	Method
Density	kg/m ³	20 ± 2.0	internal
Impact Sound Reduction	dB	≥ 19 (2mm)	BSEN ISO-140-8
Temperature Stability (unloaded)	°C	75	internal
Thermal Conductivity of PE Foam measured at 10°C	W/m k	0.045	DIN 4108
Thermal Resistance of PE Foam	m ² k/W	0.044 (2mm) 0.067 (3mm)	DIN 4108
Maximum Compression Load	kN/m ²	≤ 20	DIN EN 1606
Resistance to Compression at 25% deformation	to/m ²	≥ 2.0	DIN 53 577
Tensile Strength, lengthwise*	N/mm ²	≥ 0.30	DIN 53 571
Tensile Strength, crosswise*	N/mm ²	≥ 0.15	DIN 53 571
Elongation at break, lengthwise*	%	≥ 100	DIN 53 571
Elongation at break, crosswise*	%	≥ 80	DIN 53 571

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool, L24 8RL

Tel: 0151 495 3434

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com


Simply Better

Light
Traffic

Wood



Best for



Available in

Code	QAU-UBB-02
Size	1m x 15m (15m ²)
Thickness	2mm
Code	QAU-UBB-03
Size	1m x 15m (15m ²)
Thickness	3mm
Code	QAU-UBB-05
Size	1m x 120m (120m ²)
Thickness	2mm
Code	AWC15
Size	1m x 15m (15m ²)
Thickness	2.5mm