according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive



BUILDING TRUST

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Everbuild Stick 2 Spray Contact Adhesive

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company

Site 41

Knowsthorpe Way

Cross Green Industrial Estate

Leeds

West Yorkshire LS9 0SW

United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone num-

ber

: 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive





BUILDING TRUST

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated

area.

P280 Wear protective gloves/ eye protection/ face

protection.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accord-

ance with local regulation.

Hazardous components which must be listed on the label:

• 200-662-2 acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Registration number		
acetone	Flam. Liq.2; H225	>= 10 - < 20

Revision Date 10.07.2017

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive





Print Date 10.07.2017

67-64-1 200-662-2 01-2119471330-49-XXXX	Eye Irrit.2; H319 STOT SE3; H336	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 921-024-6 01-2119475514-35-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 10 - < 20
Substances with a workplace exposure limit :		
petroleum gases, liquefied 68476-85-7 270-704-2	Flam. Gas1; H220	>= 25 - < 40

Version 0.0

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

: Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

: Do not induce vomiting without medical advice. If swallowed

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms Excessive lachrymation

> Erythema **Dermatitis** Loss of balance

Vertigo


See Section 11 for more detailed information on health effects

and symptoms.

: irritant effects Risks

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







Version 0.0 Print Date 10.07.2017

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: Water

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







Print Date 10.07.2017



Revision Date 10.07.2017 Version 0.0

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
petroleum gases, liquefied	68476-85-7	TWA	1.000 ppm 1.750 mg/m3	GB EH40
		STEL	1.250 ppm 2.180 mg/m3	GB EH40
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	GB EH40

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive





Revision Date 10.07.2017 Version 0.0

Print Date 10.07.2017

STEL 1.500 ppm GB EH40 3.620 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers).

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties


9.1 Information on basic physical and chemical properties

Appearance : Aerosol containing a compressed gas

Colour : amber

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







Print Date 10.07.2017

Odour : characteristic

Odour Threshold : No data available

Flash point : -60 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit : 0 %(V)

Upper explosion limit : 13 %(V)

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : 7

Melting point/range / Freez-

ing point

Boiling point/boiling range

: No data available

: No data available

Vapour pressure : 34,6637 hPa

Density : 0,84 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Viscosity, dynamic

: No data available

ynamic : No data available

Viscosity, kinematic : 20,5 mm2/s

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive









Print Date 10.07.2017

Revision Date 10.07.2017 Version 0.0

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): 20.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity


Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







Version 0.0

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to fish : LC50: > 5.000 mg/l, 96 h, Fish

Toxicity to daphnia and other

aquatic invertebrates

Toxicity to algae

: EC50: 12,700 mg/l, 48 h, Daphnia (water flea)

: ErC50: > 530 mg/l, 96 h, Pseudokirchneriella subcapitata

(green algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

Country GB 10000006978 9 / 13

Revision Date 10.07.2017

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive





Version 0.0

Print Date 10.07.2017

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional legal authority requirements.

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1950 **14.2 UN proper shipping name** : AEROSOLS

14.3 Transport hazard : 2

class(es)

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D) 14.5 Environmental hazards : no

IATA

14.1 UN number : 1950

14.2 UN proper shipping name : Aerosols, flammable

14.3 Transport hazard : 2.1

class(es)

Labels : 2.1 **14.5 Environmental hazards** : no

IMDG

14.1 UN number : 1950 14.2 UN proper shipping name : AEROSOLS

 14.3 Class
 : 2.1

 Labels
 : 2.1

 EmS Number 1
 : F-D

 EmS Number 2
 : S-U

 14.5 Marine pollutant
 : no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Revision Date 10.07.2017

according to Regulation (EC) No. 1907/2006









Print Date 10.07.2017

Version 0.0

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **Prohibition/Restriction**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Banned and/or restricted (petroleum gases, liquefied)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of maior-accident hazards involving dangerous substances.

joi-accident nazarus involving da	ingerous substances.		
18	Liquefied extremely flam- mable gases (including LPG) and natural gas	Quantity 1 50 t	Quantity 2 200 t
P3a	FLAMMABLE AEROSOLS	150 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar	2.500 t	25.000 t

flammability and environmental hazards as the products referred to in points (a) to (d)

properties as regards


VOC-CH (VOCV) : 50 %

VOC-EU (solvent) : 50 %

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture:

Environmental Protection Act 1990 & Subsidiary Regulations Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations

(COSHH)

May be subject to the Control of Major Accident Hazards

Regulations (COMAH), and amendments.

Other regulations : 75/324/EEC

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic Chronic aquatic toxicity Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Flam. Gas Flammable gases Flam. Liq. Flammable liquids Skin Irrit. Skin irritation

STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

> Dangereuses par Route Chemical Abstracts Service

CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration **GHS** Globally Harmonized System

International Air Transport Association **IATA**

International Maritime Code for Dangerous Goods **IMDG**

Median lethal dosis (the amount of a material, given all at once, which LD50

causes the death of 50% (one half) of a group of test animals)

Median lethal concentration (concentrations of the chemical in air that LC50

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL**

Persistent, bioaccumulative and toxic **PBT**

according to Regulation (EC) No. 1907/2006

Everbuild Stick 2 Spray Contact Adhesive







Revision Date 10.07.2017

Version 0.0 Print Date 10.07.2017

PNEC Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament and of the **REACH**

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!