

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 100001346 Issue date: 07/03/2022 Version: 0.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : PVC Spray Cleaner

Type of product : Detergent Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use, Professional use

Use of the substance/mixture : Cleaning agent

#### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

#### Supplier

Soudal N.V. Everdongenlaan 18-20 2300 Turnhout Belgium

T +32 14 42 42 31 - F +32 14 42 65 14 sds@soudal.com - www.Soudal.com

## 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS09

Signal word (CLP)

: Danger

: hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; acetone; n-butyl acetate Contains

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P271 - Use only outdoors or in a well-ventilated area.

P391 - Collect spillage. P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**EUH-statements** EUH066 - Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	EC-No.: 920-750-0 REACH-no: 01-2119473851- 33	≥ 25 – < 50	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH066
ethanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	≥ 25 – < 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
acetone substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-	≥ 10 – < 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	≥ 5 – < 10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
butane substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	≥ 1 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
propane substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	≥1-<5	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
ethanol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-	( 50 ≤C < 100) Eye Irrit. 2, H319

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

07/03/2022 (Issue date) EU - en 3/19

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn,

even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

07/03/2022 (Issue date) EU - en 4/19

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

butane (106-97-8)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan	
OEL STEL	2370 mg/m³	
OEL STEL [ppm]	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
propane (74-98-6)		
Belgium - Occupational Exposure Limits		
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)	
OEL TWA [ppm]	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
ethanol (64-17-5)		
Belgium - Occupational Exposure Limits		
Local name	Alcool éthylique # Ethanol	
OEL TWA	1907 mg/m³	
OEL TWA [ppm]	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
acetone (67-64-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	1210 mg/m³	
IOEL TWA [ppm]	500 ppm	
Belgium - Occupational Exposure Limits	Belgium - Occupational Exposure Limits	
OEL TWA	594 mg/m³	
OEL TWA [ppm]	246 ppm	
OEL STEL	1187 mg/m³	
OEL STEL [ppm]	492 ppm	
n-butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	241 mg/m³	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m³
IOEL STEL [ppm]	150 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	238 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	712 mg/m³
OEL STEL [ppm]	150 ppm

# 8.1.2. Recommended monitoring procedures

No additional information available

## 8.1.3. Air contaminants formed

No additional information available

## 8.1.4. DNEL and PNEC

hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2035 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	699 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	608 mg/m³	
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day	
ethanol (64-17-5)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	343 mg/kg bw/day	
Long-term - systemic effects, inhalation	950 mg/m³	
DNEL/DMEL (General population)	DNEL/DMEL (General population)	
Long-term - systemic effects,oral	87 mg/kg bw/day	
Long-term - systemic effects, inhalation	114 mg/m³	
Long-term - systemic effects, dermal	206 mg/kg bw/day	
PNEC (Water)		
PNEC aqua (freshwater)	0,96 mg/l	
PNEC aqua (marine water)	0,79 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3,6 mg/kg dwt	
PNEC sediment (marine water)	2,9 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,63 mg/kg dwt	
PNEC (Oral)	PNEC (Oral)	
PNEC oral (secondary poisoning)	0,38	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethanol (64-17-5)		
PNEC (STP)		
PNEC sewage treatment plant	580 mg/l	
acetone (67-64-1)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	2420 mg/m³	
Long-term - systemic effects, dermal	186 mg/kg bw/day	
Long-term - systemic effects, inhalation	1210 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	62 mg/kg bw/day	
Long-term - systemic effects, inhalation	200 mg/m³	
Long-term - systemic effects, dermal	62 mg/kg bw/day	
PNEC (Water)		
PNEC aqua (freshwater)	10,6 mg/l	
PNEC aqua (marine water)	1,06 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	30,4 mg/kg dwt	
PNEC sediment (marine water)	3,04 mg/kg dwt	
PNEC (Soil)		
PNEC soil	29,5 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
n-butyl acetate (123-86-4)		
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	11 mg/kg bw/day	
Acute - systemic effects, inhalation	600 mg/m³	
Acute - local effects, inhalation	600 mg/m³	
Long-term - systemic effects, dermal	11 mg/kg bw/day	
Long-term - systemic effects, inhalation	300 mg/m³	
Long-term - local effects, inhalation	300 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, dermal	6 mg/kg bw/day	
Acute - systemic effects, inhalation	300 mg/m³	
Acute - systemic effects, oral	2 mg/kg bw/day	
Acute - local effects, inhalation	300 mg/m³	
Long-term - systemic effects,oral	2 mg/kg bw/day	
Long-term - systemic effects, inhalation	35,7 mg/m³	
Long-term - systemic effects, dermal	6 mg/kg bw/day	
Long-term - local effects, inhalation	35,7 mg/m³	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)		
PNEC (Water)	PNEC (Water)	
PNEC aqua (freshwater)	0,18 mg/l	
PNEC aqua (marine water)	0,018 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0,981 mg/kg dwt	
PNEC sediment (marine water)	0,098 mg/kg dwt	
PNEC (Soil)	PNEC (Soil)	
NEC soil 0,09 mg/kg dwt		
PNEC (STP)		
PNEC sewage treatment plant	35,6 mg/l	

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):







#### 8.2.2.1. Eye and face protection

#### Eye protection:

Safety glasses (EN 166)

## 8.2.2.2. Skin protection

#### Skin and body protection:

Protective clothing (EN 14605 or EN 13034)

#### Hand protection:

Protective gloves against chemicals (EN 374)

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colour : Not available
Appearance : Aerosol.
Odour : Not available
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

: Not applicable

**Explosive limits** : Not available : Not available Lower explosion limit : Not available Upper explosion limit : Not applicable Flash point : Not available Auto-ignition temperature Not available Decomposition temperature рΗ : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure Vapour pressure at 50°C : Not available Density : 0,74 g/cm3 (20°C) Relative density : Not available Relative vapour density at 20°C : Not available

#### 9.2. Other information

Particle characteristics

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 101,5 %

9.2.2. Other safety characteristics

VOC content : 100 %

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

07/03/2022 (Issue date) EU - en 9/19

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

,	Not classified Not classified
butane (106-97-8)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value of similar product, Inhalation (gases))
propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics
LD50 oral	> 5840 mg/kg bodyweight
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal	> 2920 mg/kg bodyweight
LC50 Inhalation - Rat	> 23,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 23300 mg/l
ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg bodyweight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	124,7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	0,74 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation :	Not classified
butane (106-97-8)	
рН	No data available in the literature
propane (74-98-6)	
рН	No data available in the literature
ethanol (64-17-5)	
рН	7 (789 g/l, 20 °C)
acetone (67-64-1)	
рН	5 – 6 (20 °C)
n-butyl acetate (123-86-4)	
pH	6,2 (0.53 %, 20 °C)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  STOT-repeated exposure : Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8) Viscosity, kinematic   No data available in the literature  propane (74-98-6) Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   0,715 - 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5) Viscosity, kinematic   1,6 mm²/s (20 °C)  acetone (67-64-1)	Serious eye damage/irritation :	Causes serious eye irritation.
priopane (74-98-6) pH No data available in the literature  ethanol (64-17-5) pH 7(789 g/l, 20 °C)  acotone (67-64-1) pH 5-6 (20 °C)  mount (23-86-4) pH 6.2 (0.53 %, 20 °C)  Respitatory or skin sensitisation : Not dassified Germ cell mutagenicity : Not dassified Germ cell mutagenicity : Not dassified Germ cell mutagenicity : Not dassified Reproductive toxicity : Not dassified Reproductive toxicity : Not dassified STOTangle apposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-angle exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-angle exposure Nay cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-angle exposure : Not dassified hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics NOAEC (inhalation, rat, vapour, 90 days) 24,3 mg/l air Animat: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity, 90-Day Study) Aspiration hazard : Not dassified  PVC Spray Cleaner Vaporizer Aerosol  butane (106-97-8) Viscosity, kinematic No data available in the literature  propane (74-98-6) Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic No data available in the literature  propane (74-98-6) Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic No data available in the literature  propane (74-98-6) Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic No data available in the literature	butane (106-97-8)	
pH No data available in the literature  ethanol (64-17-5) pH 7 (789 g/l. 20 °C)  acetone (67-64-1) pH 5-6 (20 °C)  n-butyl acetate (123-86-4) pH 6.2 (0.53 %, 20 °C)  Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Germ cell mutagenicity : Not classified Reproductive toxicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  Acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  BOD-stotage exposure May cause drowsiness or dizziness.  BOD-stotage exposure Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days) 24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Appiration hazard : Not classified  PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8) Viscosity, kinematic No data available in the literature  propane (74-98-6) Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic No data available in the literature	рН	No data available in the literature
pH 7 (789 gil, 20 °C)  acetone (67-64-1) pH 5 - 6 (20 °C)  n-butyl acetate (123-86-4) pH 6.2 (0.53 %, 20 °C) Respiratory or skin sensitisation : Not classified Garrinogenicity : Not classified Garrinogenicity : Not classified Reproductive toxicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  NOT-single exposure   May cause drowsiness or dizziness.  NOT-single exposure   May cause drowsiness or dizziness.  NOT-single exposure   Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard   Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8)  Viscosity, kinematic   No data available in the literature  propane (74-98-6)  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   0,715 – 0,786 mm²/s Temp: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic   1,6 mm²/s (20 °C)  acetone (67-64-1)	propane (74-98-6)	
pH   7 (789 g/l, 20 °C)  acetone (67-64-1) pH   5 - 6 (20 °C)  n-butyl acetate (123-86-4) pH   6.2 (0.53 %, 20 °C) Respiratory or skin sensitisation   Not classified   Germ cell mutagenicity   Not classified   Reproductive toxicity   Not classified   STOT-single exposure   May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  STOT-single exposure   May cause drowsiness or dizziness.  STOT-single exposure   Not classified   hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard   Not classified   PVC Spray Cleaner  Vaporizer   Aerosol    butane (106-97-8)  Viscosity, kinematic   No data available in the literature    propane (74-98-6)  Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics    Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics    Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics    Viscosity, kinematic   No data available in the literature    hydrocarbons, C7-C9, n-alkan	рН	No data available in the literature
acetone (67-64-1) pH   5 - 6 (20 °C) n-butyl acetate (123-86-4) pH   6,2 (0.53 %, 20 °C) Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Germ cell mutagenicity : Not classified StoTo-single exposure : May cause drowsiness or dizziness. hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-ringle exposure   May cause drowsiness or dizziness.  Thoutyl acetate (123-86-4) STOT-repated exposure   May cause drowsiness or dizziness.  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8) Viscosity, kinematic   No data available in the literature  propane (74-98-6) Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature	ethanol (64-17-5)	
pH   5 - 6 (20 °C)  n-butyl acetate (123-86-4)  pH   6,2 (0.53 %, 20 °C)  Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Germ cell mutagenicity : Not classified Germ cell control	рН	7 (789 g/l, 20 °C)
n-butyl acetate (123-86-4) pH	acetone (67-64-1)	
pH 6,2 (0.53 %, 20 °C)  Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Germ cell mutagenicity : Not classified Reproductive toxicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acctate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acctate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acctate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8) Viscosity, kinematic   No data available in the literature  propane (74-98-6) Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature	рН	5 – 6 (20 °C)
Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  STOT-repeated exposure   Not classified hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8)  Viscosity, kinematic   No data available in the literature  propane (74-98-6)  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   0.715 - 0.786 mm²/s Temp.: other: Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic   1.6 mm²/s (20 °C)  acetone (67-64-1)	n-butyl acetate (123-86-4)	
Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-repeated exposure   May cause drowsiness or dizziness.  TOT-repeated exposure   Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8) Viscosity, kinematic   No data available in the literature  propane (74-98-6) Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   0,715 - 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5) Viscosity, kinematic   1,6 mm²/s (20 °C)  acetone (67-64-1)	рН	6,2 (0.53 %, 20 °C)
Carcinogenicity : Not classified Reproductive toxicity : Not classified STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure   May cause drowsiness or dizziness.  STOT-repeated exposure   Stot classified   hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard   Not classified   PVC Spray Cleaner  Vaporizer   Aerosol   butane (106-97-8) Viscosity, kinematic   No data available in the literature   propane (74-98-6) Viscosity, kinematic   No data available in the literature   hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic   0,715 - 0,786 mm²/s Temp.: other: Parameter: 'kinematic viscosity (in mm²/s)'   ethanol (64-17-5) Viscosity, kinematic   1,6 mm²/s (20 °C)   acetone (67-64-1)	Respiratory or skin sensitisation :	Not classified
Reproductive toxicity : Not classified : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  STOT-single exposure   May cause drowsiness or dizziness.  acetone (67-64-1)  STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure   May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure   May cause drowsiness or dizziness.  STOT-repeated exposure   Stot classified   hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8)  Viscosity, kinematic   No data available in the literature  propane (74-98-6)  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   No data available in the literature  hydrocarbons   No data available in the literature	Germ cell mutagenicity :	Not classified
STOT-single exposure : May cause drowsiness or dizziness.  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1)  STOT-single exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure May cause drowsiness or dizziness.  TOT-single exposure May cause drowsiness or dizziness.  STOT-repeated exposure Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days) 24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8)  Viscosity, kinematic No data available in the literature  propane (74-98-6)  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	Carcinogenicity :	Not classified
hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  STOT-single exposure  May cause drowsiness or dizziness.  acetone (67-64-1)  STOT-single exposure  May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure  May cause drowsiness or dizziness.  STOT-repeated exposure  Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)  Aspiration hazard  Not classified  PVC Spray Cleaner  Vaporizer  Aerosol  butane (106-97-8)  Viscosity, kinematic  No data available in the literature  propane (74-98-6)  Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	Reproductive toxicity :	Not classified
STOT-single exposure May cause drowsiness or dizziness.  acetone (67-64-1) STOT-single exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4) STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure : Not classified hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics NOAEC (inhalation, rat, vapour, 90 days) 24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) Aspiration hazard : Not classified  PVC Spray Cleaner Vaporizer Aerosol  butane (106-97-8) Viscosity, kinematic No data available in the literature  propane (74-98-6) Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)' ethanol (64-17-5) Viscosity, kinematic 1,6 mm²/s (20 °C) acetone (67-64-1)	STOT-single exposure :	May cause drowsiness or dizziness.
acetone (67-64-1)  STOT-single exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure May cause drowsiness or dizziness.  STOT-repeated exposure : Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days) 24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8)  Viscosity, kinematic No data available in the literature  propane (74-98-6)  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other.' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics
STOT-single exposure May cause drowsiness or dizziness.  n-butyl acetate (123-86-4)  STOT-single exposure May cause drowsiness or dizziness.  STOT-repeated exposure : Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days) 24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8)  Viscosity, kinematic No data available in the literature  propane (74-98-6)  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)  STOT-single exposure   May cause drowsiness or dizziness.  STOT-repeated exposure : Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)   24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard : Not classified  PVC Spray Cleaner  Vaporizer   Aerosol  butane (106-97-8)  Viscosity, kinematic   No data available in the literature  propane (74-98-6)  Viscosity, kinematic   No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic   0,715 - 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic   1,6 mm²/s (20 °C)  acetone (67-64-1)	acetone (67-64-1)	
STOT-single exposure	STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure : Not classified  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)	n-butyl acetate (123-86-4)	
hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  NOAEC (inhalation, rat, vapour, 90 days)  24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard  PVC Spray Cleaner  Vaporizer  Aerosol  butane (106-97-8)  Viscosity, kinematic  No data available in the literature  propane (74-98-6)  Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	STOT-single exposure	May cause drowsiness or dizziness.
NOAEC (inhalation, rat, vapour, 90 days)  24,3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)  Aspiration hazard: Not classified  PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8)  Viscosity, kinematic No data available in the literature  propane (74-98-6)  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	STOT-repeated exposure :	Not classified
90-Day Study)   Aspiration hazard : Not classified	hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics
PVC Spray Cleaner  Vaporizer Aerosol  butane (106-97-8)  Viscosity, kinematic No data available in the literature  propane (74-98-6)  Viscosity, kinematic No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	NOAEC (inhalation, rat, vapour, 90 days)	
Vaporizer  Aerosol  butane (106-97-8)  Viscosity, kinematic  No data available in the literature  propane (74-98-6)  Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	Aspiration hazard :	Not classified
butane (106-97-8)  Viscosity, kinematic  Propane (74-98-6)  Viscosity, kinematic  No data available in the literature  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	PVC Spray Cleaner	
Viscosity, kinematic  Propane (74-98-6)  Viscosity, kinematic  No data available in the literature  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	Vaporizer	Aerosol
propane (74-98-6)  Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	butane (106-97-8)	
Viscosity, kinematic  No data available in the literature  hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	Viscosity, kinematic	No data available in the literature
hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  Viscosity, kinematic 0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	propane (74-98-6)	
Viscosity, kinematic  0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'  ethanol (64-17-5)  Viscosity, kinematic  1,6 mm²/s (20 °C)  acetone (67-64-1)	Viscosity, kinematic	No data available in the literature
ethanol (64-17-5)         Viscosity, kinematic       1,6 mm²/s (20 °C)         acetone (67-64-1)	hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics
Viscosity, kinematic 1,6 mm²/s (20 °C)  acetone (67-64-1)	Viscosity, kinematic	0,715 – 0,786 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'
acetone (67-64-1)	ethanol (64-17-5)	
	Viscosity, kinematic	1,6 mm²/s (20 °C)
Viscosity, kinematic  No data available in the literature	acetone (67-64-1)	
··· ·· · · · · · · · · · · · · · · · ·	Viscosity, kinematic	No data available in the literature

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
Viscosity, kinematic	0,831 mm²/s (20 °C, ASTM D445: Capillary viscometer)

# 11.2. Information on other hazards

No additional information available

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

: Toxic to aquatic life with long lasting effects. Hazardous to the aquatic environment, long-term

(chronic)

Not rapidly degradable

butane (106-97-8)			
LC50 - Fish [1]	24,11 mg/l (ECOSAR, 96 h, Pisces, Fresh water, QSAR)		
EC50 96h - Algae [1]	7,71 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)		
propane (74-98-6)			
LC50 - Fish [1]	49,9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)		
EC50 96h - Algae [1]	11,89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)		
hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics		
LC50 - Fish [1]	> 3 mg/l		
EC50 - Other aquatic organisms [1]	4,6 mg/l waterflea		
EC50 - Other aquatic organisms [2]	10 mg/l		
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
ethanol (64-17-5)			
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)		
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)		
acetone (67-64-1)			
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)		
n-butyl acetate (123-86-4)			
LC50 - Fish [1]	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)		
EC50 - Crustacea [1]	44 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia sp., Static system, Fresh water, Experimental value, Locomotor effect)		
ErC50 algae	397 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 12.2. Persistence and degradability

butane (106-97-8)			
Persistence and degradability	Readily biodegradable in water.		
propane (74-98-6)			
Persistence and degradability	Readily biodegradable in water.		
ethanol (64-17-5)			
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	0,8 − 0,967 g O₂/g substance		
Chemical oxygen demand (COD)	1,7 g O <sub>2</sub> /g substance		
ThOD	2,1 g O <sub>2</sub> /g substance		
Biodegradation	84 % (% degradation (O2 consumption), 20d)		
acetone (67-64-1)			
Persistence and degradability	Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	1,43 g O <sub>2</sub> /g substance		
Chemical oxygen demand (COD)	1,92 g O₂/g substance		
ThOD	2,2 g O <sub>2</sub> /g substance		
n-butyl acetate (123-86-4)			
Persistence and degradability	Readily biodegradable in water.		
ThOD	2,21 g O₂/g substance		
12.3. Bioaccumulative potential			

#### 12.3. Bioaccumulative potential

butane (106-97-8)				
Partition coefficient n-octanol/water (Log Pow)	2,8 (Experimental value, 20 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).			
propane (74-98-6)				
Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).			
hydrocarbons, C7-C9, n-alkanes, isoalkanes,	cyclics			
Partition coefficient n-octanol/water (Log Pow)	4,85			
ethanol (64-17-5)				
Partition coefficient n-octanol/water (Log Pow)	-0,35 (Experimental value, Equivalent or similar to OECD 107, 24 °C)			
Bioaccumulative potential	Not bioaccumulative.			
acetone (67-64-1)				
BCF - Fish [1]	0,69 (Pisces, Literature study)			
Partition coefficient n-octanol/water (Log Pow)	-0,23 (Test data)			
Bioaccumulative potential	not bioaccumulable.			
n-butyl acetate (123-86-4)				
Partition coefficient n-octanol/water (Log Pow)	2,3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)			

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# 12.4. Mobility in soil

ethanol (64-17-5)			
Surface tension	22,31 mN/m (20 °C, 100 %)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,2 (log Koc, Experimental value)		
Ecology - soil	Highly mobile in soil.		
acetone (67-64-1)			
Surface tension	23,3 mN/m (20 °C)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,374 – 0,988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)		
Ecology - soil	Highly mobile in soil.		
n-butyl acetate (123-86-4)			
Surface tension	61,3 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1,268 – 1,844 (log Koc, SRC PCKOCWIN v2.0, Calculated value)		
Ecology - soil	Highly mobile in soil.		

## 12.5. Results of PBT and vPvB assessment

Component	
butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Ecology - waste materials : Avoid release to the environment.

07/03/2022 (Issue date) EU - en 14/19

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

European List of Waste (LoW) code

: 16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

20 01 29\* - detergents containing dangerous substances

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID			
14.1. UN number or ID number							
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950			
14.2. UN proper shippin	g name						
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS			
Transport document descr	iption						
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS			
14.3. Transport hazard class(es)							
2.1	2.1	2.1	2.1	2.1			
2	2	2	2	<b>1 1 1 1 1 1 1 1 1 1</b>			
14.4. Packing group							
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable			
14.5. Environmental hazards							
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes			
No supplementary information	n available		1	1			

## 14.6. Special precautions for user

#### **Overland transport**

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14Special provisions for carriage - Loading, unloading: CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200

07/03/2022 (Issue date) EU - en 15/19

#### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

#### Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

#### Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

#### Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200
Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

EU restriction list (REA	U restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(a)	PVC Spray Cleaner; hydrocarbons, C7-C9, n- alkanes, isoalkanes, cyclics; ethanol; acetone ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)				
Reference code	Applicable on	Entry title or description		
3(b)	PVC Spray Cleaner; hydrocarbons, C7-C9, n- alkanes, isoalkanes, cyclics; ethanol; acetone ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10		
3(c)	PVC Spray Cleaner; hydrocarbons, C7-C9, n- alkanes, isoalkanes, cyclics	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1		

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### VOC Directive (2004/42)

VOC content : 100 %

#### **Detergent Regulation (648/2004)**

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%

#### **Explosives Precursors Regulation (2019/1148)**

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name		Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list of competent authorities and national contact points en.pdf

## **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# **SECTION 16: Other information**

Abbreviations and acronyms:			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:			
Aerosol 1	Aerosol, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H304	May be fatal if swallowed and enters airways.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
H411	Toxic to aquatic life with long lasting effects.		
Press. Gas (Liq.)	Gases under pressure : Liquefied gas		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Aerosol 1	H222;H229	On basis of test data		
Eye Irrit. 2	H319	Calculation method		
STOT SE 3	H336	Calculation method		
Aquatic Chronic 2	H411	Calculation method		

Safety Data Sheet (SDS), EU-2022-2

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.