



Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 25/10/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Superfast Plus 20 ml & 50 ml
Product code : MS 740130
Type of product : ethyl 2-cyanoacrylate

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Use of the substance/mixture : Adhesives
Binding agent
Function or use category : Adhesives, binding agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

C-Tec NI Limited
Unit 6 Ashtree Enterprise Park,
Rathfriland Road, Newry, Co. Down
N. Ireland BT34 1
T +44 (0) 28 3083 4892

info@ct1.com - ww.ct1.com

1.4. Emergency telephone number

Emergency number : +44 (0) 28 3083 4892 (Monday – Friday 9am - 5pm)
Outside of normal office hours please call emergency number below.

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation H335
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: ethyl 2-cyanoacrylate

Hazard statements (CLP)

: H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H335 - May cause respiratory irritation.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P261 - Avoid breathing mist, spray, vapours.

P271 - Use only outdoors or in a well-ventilated area.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH202 - Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Child-resistant fastening

: Not applicable

Tactile warning

: Not applicable

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl 2-cyanoacrylate	CAS-No.: 7085-85-0 EC-No.: 230-391-5 EC Index-No.: 607-236-00-9 REACH-no.: 01-2119527766-29	50 - 100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
1,4-dihydroxybenzene; hydroquinone; quinol	CAS-No.: 123-31-9 EC-No.: 204-617-8 EC Index-No.: 604-005-00-4 REACH-no.: 01-2119524016-51	0.01 - 0.1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 2, H351 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
ethyl 2-cyanoacrylate	CAS-No.: 7085-85-0 EC-No.: 230-391-5 EC Index-No.: 607-236-00-9 REACH-no.: : 01-2119527766-29	(10 ≤C ≤ 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Exothermic reaction on contact with : Skin. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Shortness of breath. Coughing. May cause respiratory irritation.
Symptoms/effects after skin contact	: irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: redness, itching, tears. stinging. Eye irritation.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting. Irritation of the oral mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Precautionary measures fire	: Eliminate all ignition sources if safe to do so. Evacuate area.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate spillage area. Avoid breathing mist, spray, vapours. Avoid contact with skin and eyes.

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not allow product to spread into the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing mist, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Incompatible products : Strong bases.
Packaging materials : Keep only in the original container in a cool, well-ventilated place away from combustible materials.

7.3. Specific end use(s)

Adhesives.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethyl 2-cyanoacrylate (7085-85-0)	
Austria - Occupational Exposure Limits	
Local name	Cyanacrylsäureethylester
MAK (OEL TWA)	9 mg/m ³
MAK (OEL TWA) [ppm]	2 ppm
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	2-Cyanoacrylate d'éthyle # Ethyl-2-cyanoacrylaat
OEL TWA	1.04 mg/m ³
OEL TWA [ppm]	0.2 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
Local name	Etil-cijanoakrilat

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl 2-cyanoacrylate (7085-85-0)	
KGVI (OEL STEL)	1.5 mg/m ³
KGVI (OEL STEL) [ppm]	0.3 ppm
Remark	Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Ethyl-2-kyanakrylát (Ethyl-2-kyanprop-2-enoát)
PEL (OEL TWA)	1 mg/m ³
PEL (OEL TWA) [ppm]	0.2 ppm
NPK-P (OEL C)	2 mg/m ³
NPK-P (OEL C) [ppm]	0.4 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Ethylcyanoacrylat
OEL TWA [1]	10 mg/m ³
OEL TWA [2]	2 ppm
Regulatory reference	BEK nr 202 af 21/02/2023
Estonia - Occupational Exposure Limits	
Local name	Etüültsüanoakrülaat
OEL TWA	10 mg/m ³
OEL TWA [ppm]	2 ppm
OEL STEL	20 mg/m ³
OEL STEL [ppm]	4 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	Etyyli-2-syanoakrylaatti
HTP (OEL TWA) [1]	1 mg/m ³
HTP (OEL TWA) [2]	0.2 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
Ireland - Occupational Exposure Limits	
Local name	Cyanoacrylate, Ethyl [Ethyl cyanoacrylate]
OEL TWA [2]	0.2 ppm
OEL STEL [ppm]	1 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Lithuania - Occupational Exposure Limits	
Local name	Etil-2-ciankrilatas
IPRV (OEL TWA)	10 mg/m ³
IPRV (OEL TWA) [ppm]	2 ppm

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl 2-cyanoacrylate (7085-85-0)	
TPRV (OEL STEL)	20 mg/m ³
TPRV (OEL STEL) [ppm]	4 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	2-Cyjanoakrylan etylu
NDS (OEL TWA)	1 mg/m ³
NDSch (OEL STEL)	2 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Cianoacrilato de etilo
OEL TWA [ppm]	0.2 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Spain - Occupational Exposure Limits	
Local name	Cianoacrilato de etilo
VLA-ED (OEL TWA) [2]	0.2 ppm
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etyl-2-cyanoakrylat
NGV (OEL TWA)	10 mg/m ³
NGV (OEL TWA) [ppm]	2 ppm
KTV (OEL STEL)	20 mg/m ³
KTV (OEL STEL) [ppm]	4 ppm
Remark	M (Medicinska kontroller kan krävas för hantering av ämnet. Se vidare föreskrifterna om medicinska kontroller i arbetslivet. För vissa ämnen ska arbetsgivaren erbjuda läkarundersökning och för andra ämnen gäller krav på periodisk läkarundersökning och tjänstbarhetsbedömning); S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Ethyl cyanoacrylate
WEL STEL (OEL STEL)	1.5 mg/m ³
WEL STEL (OEL STEL) [ppm]	0.3 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Etylsýanoakrylát

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl 2-cyanoacrylate (7085-85-0)	
OEL TWA	10 mg/m ³
OEL TWA [ppm]	2 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
Switzerland - Occupational Exposure Limits	
Local name	2-Cyanoacrylate d'éthyle / Cyanacrylsäureethylester [Ethyl-2-cyanoacrylat]
MAK (OEL TWA) [1]	9 mg/m ³
MAK (OEL TWA) [2]	2 ppm
Critical toxicity	VRS, Peau / OAW, Haut
Regulatory reference	www.suva.ch, 01.01.2023
1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)	
Austria - Occupational Exposure Limits	
Local name	1,4-Dihydroxybenzol (Hydrochinon)
MAK (OEL TWA)	2 mg/m ³ (E)
MAK (OEL STEL)	4 mg/m ³ (E, 8x 5(Mow) min)
Remark	S. Krebserzeugend: III B
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Hydroquinone # Hydrochinon
OEL TWA	1 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
Local name	Hidrokinon; 1,4-dihidroksibenzen; kinol
GVI (OEL TWA) [1]	0.5 mg/m ³
Remark	Alergen koža (tvar koja može izazvati alergijsku reakciju na koži (H317))
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	1,4-Dihydroxybenzen (Hydrochinon)
PEL (OEL TWA)	2 mg/m ³
NPK-P (OEL C)	4 mg/m ³
Remark	D - při expozici se významně uplatňuje pronikání faktoru kůží, I - dráždí sliznice (oči, dýchací cesty), respektive kůži, S - látka má senzibilizující účinek (s větou H317, H334).
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Hydroquinon (p-Benzendiol)
OEL C	2 mg/m ³
Remark	K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Regulatory reference	BEK nr 202 af 21/02/2023

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)	
Estonia - Occupational Exposure Limits	
Local name	Hüdrokinoon (1,4-benseendiool)
OEL TWA	0.5 mg/m ³
OEL STEL	1.5 mg/m ³
Remark	S (Sensibiliseeriv aine), 5 (Kinoon võib redutseeruda hüdrokinooniks, mis muutub õhuhapniku toimel kergesti p-bensokinooniks)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 21.12.2022, 3)
Finland - Occupational Exposure Limits	
Local name	Hydrokinoni
HTP (OEL TWA) [1]	0.5 mg/m ³
HTP (OEL STEL)	2 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	Hydroquinone
VME (OEL TWA)	2 mg/m ³
Remark	Valeurs recommandées/admises; substance classée cancérogène de catégorie 2 et mutagène de catégorie 2
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Υδροκινόνη
OEL TWA	2 mg/m ³
OEL STEL	4 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Ireland - Occupational Exposure Limits	
Local name	Hydroquinone [p-Dihydroxybenzene]
OEL TWA [1]	0.5 mg/m ³
Remark	Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
Lithuania - Occupational Exposure Limits	
Local name	Hidrochinonas
IPRV (OEL TWA)	0.5 mg/m ³
TPRV (OEL STEL)	1.5 mg/m ³
Remark	K (kancerogeninis poveikis); M (mutageninis poveikis); J (jautrinantis poveikis); p-benzchinonas (chinonas) yra oksiduojanti medžiaga, kuri redukuojasi į hidrochinoną. Hidrochinonas vėl lengvai virsta p-benzchinonu, pvz., veikiamas atmosferos deguonies.

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)	
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Hydrochinon
NDS (OEL TWA)	1 mg/m ³
NDSch (OEL STEL)	2 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286 wraz z późn. zm.
Portugal - Occupational Exposure Limits	
Local name	Hidroquinona
OEL TWA	1 mg/m ³
Remark	SC (Agente com potencial para produzir sensibilização pela via cutânea); A3 (Agente carcinogénico confirmado nos animais de laboratório con relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	1,4-dihidroxibenzen/Hidrochinonă
OEL TWA	1 mg/m ³
OEL STEL	2 mg/m ³
Remark	C2 - susceptibil de a provoca apariția cancerului; M2 - susceptibil de a provoca anomalii genetice
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Hydrochinón (benzén-1,4-diol)
NPHV (OEL TWA) [1]	2 mg/m ³
Remark	K - znamená, že faktor môže byť ľahko absorbovaný kožou
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Spain - Occupational Exposure Limits	
Local name	Hidroquinona
VLA-ED (OEL TWA) [1]	2 mg/m ³
Remark	Sen (Sensibilizante).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
Local name	Hydrokinon
NGV (OEL TWA)	0.5 mg/m ³
KTV (OEL STEL)	1.5 mg/m ³

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)	
Remark	S (Ämnet är sensibiliserande. Sensibiliserande ämnen kan ge allergi eller annan överkänslighet. Överkänslighetsbesvären drabbar främst huden eller andningsorganen. Överkänslighet innebär att man reagerar vid kontakt med ämnen som normalt inte ger besvär. Allergi är en undergrupp av överkänslighet som orsakas av reaktioner i kroppens immunsystem. Särskilt låga gränsvärden har fastställts för ämnen med mer uttalat luftvägssensibiliserande egenskaper. Några ämnen med starkt sensibiliserande egenskaper får endast hanteras efter tillstånd från Arbetsmiljöverket, se föreskrifterna om kemiska arbetsmiljörisker. Dessa ämnen har inga gränsvärden men i vissa fall riktvärden); V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas); 10 (p-Bensokinon, kinon, kan genom reduktion övergå till hydrokinon. Hydrokinon kan lätt återbildas till p-bensokinon genom luftoxidation)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Hydroquinone
WEL TWA (OEL TWA) [1]	0.5 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Iceland - Occupational Exposure Limits	
Local name	Hýdrókínón (p-bensendíól)
OEL TWA	0.5 mg/m ³
OEL STEL	2 mg/m ³
Remark	O (efnið er ofnæmisvaldandi)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 1296/2012)
Norway - Occupational Exposure Limits	
Local name	Hydrokinon
Grenseverdi (OEL TWA) [1]	0.5 mg/m ³
Remark	A: Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt; K: Kjemikalier som skal betraktes som kreftfremkallende.
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Hydroquinone / 1,4-Dihydroxybenzol [Hydrochinon]
MAK (OEL TWA) [1]	2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	2 mg/m ³ (i) / (e)
Critical toxicity	Yeux / Auge
Notation	R, S, C2, M2 / H, S, C2, M2
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

ethyl 2-cyanoacrylate (7085-85-0)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	9.25 mg/m ³
Acute - local effects, inhalation	9.25 mg/m ³
Long-term - systemic effects, inhalation	9.25 mg/m ³
Long-term - local effects, inhalation	9.25 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	9.25 mg/m ³
Acute - local effects, inhalation	9.25 mg/m ³
Long-term - systemic effects, inhalation	9.25 mg/m ³
Long-term - local effects, inhalation	9.25 mg/m ³
1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	3.33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.1 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.05 mg/m ³
Long-term - systemic effects, dermal	1.66 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.57 µg/l
PNEC aqua (marine water)	0.057 µg/l
PNEC aqua (intermittent, freshwater)	1.34 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	4.9 µg/kg dw
PNEC sediment (marine water)	0.49 µg/kg dw
PNEC (Soil)	
PNEC soil	0.64 µg/kg dw
PNEC (STP)	
PNEC sewage treatment plant	0.71 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety goggles	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
Wear protective clothing	EN 14605

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.44		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Full face mask	Filter A1/B1, Type A - High-boiling (>65 °C) organic compounds	Mist formation, Moist condition, Protection for Liquid particles, Vapour protection	EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colour	: Colourless.
Odour	: Characteristic odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 149 °C
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 80 – 93.4 °C Closed cup
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: ≈ 90 mm ² /s
Viscosity, dynamic	: ≈ 100 mPa·s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.27 mbar
Vapour pressure at 50°C	: < 0.7 bar
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: ≈ 1.05
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 3 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Acute toxicity (inhalation) : Not classified

ethyl 2-cyanoacrylate (7085-85-0)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
--------------------	---

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

ethyl 2-cyanoacrylate (7085-85-0)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Superfast Plus 20 ml & 50 ml

Viscosity, kinematic : $\approx 90 \text{ mm}^2/\text{s}$

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified
Not rapidly degradable

1,4-dihydroxybenzene; hydroquinone; quinol (123-31-9)

LC50 - Fish [1]	0.638 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	0.134 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.061 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
NOT SUBJECT	NOT SUBJECT (Not subject to the provisions of IMDG but may be subject to provisions governing the transport of dangerous goods by other modes)		NOT SUBJECT
14.1. UN number or ID number			
UN 3334	UN 3334	UN 3334	UN 3334
14.2. UN proper shipping name			
Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate)	AVIATION REGULATED LIQUID, N.O.S. (ethyl 2-cyanoacrylate)	Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate)	aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate)
Transport document description			
UN 3334 Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate), 9	UN 3334 AVIATION REGULATED LIQUID, N.O.S. (ethyl 2-cyanoacrylate), 9	UN 3334 Aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate), 9, III	UN 3334 aviation regulated liquid, n.o.s. (ethyl 2-cyanoacrylate), 9
14.3. Transport hazard class(es)			
9	9	9	9
Not applicable			Not applicable
14.4. Packing group			
Not applicable	Not applicable	III	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M11
EAC code : 2Z

Transport by sea

Special provisions (IMDG) : 960
Stowage category (IMDG) : None
Properties and observations (IMDG) : Not subject to the provisions of this Code but may be subject to provisions governing the transport of dangerous goods by other modes.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A27
ERG code (IATA) : 9A

Inland waterway transport

Classification code (ADN) : M11

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 3 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Class for fire hazard	: Class III-1
Store unit	: 50 liter
Classification remarks	: Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK)	: LK 10/12 - Liquids
--------------------	----------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH202	Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.

Superfast Plus 20 ml & 50 ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.