

Page 1/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML
- · Article number: 441.0800002.076-288055
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · **Product category** Paint remover
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Wickes

Vision House

19 Colonial Way

WD24 4JL

United Kingdom

Tel: +44 (0)330 123 4123

e-mail: compliance@wickes.co.uk

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 3	<i>H412</i>	Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

· Hazard pictograms





GHS02

· Signal word Danger

· Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

butan-1-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225	25-<50%
Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	EUH066 Eye Irrit. 2, H319; STOT SE 3, H336	
EINECS: 200-827-9	propane Flam. Gas 1A, H220	10-<12.5%
Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	,	Contd. on page

GB

(Contd. of page 1)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

		(Contd. of page
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	_ 10-<12.59
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide © Carc. 2, H351	2.5-<5%
CAS: 9004-70-0	cellulose nitrate Expl. 1.1, H201	<2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<2.5%

· Additional information:

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

 During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

(Contd. on page 4)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

· Protective equipment: Mouth respiratory protective device.

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

13463-67-	titanium dioxide	(Contd. of pa
	-term value: 10* 4** mg/m³	
	l inhalable **respirable	
71-36-3 bu		
	t-term value: 154 mg/m³, 50 ppm	
Sk		
DNELs		
67-64-1 ac		
Oral	DNEL 62 mg/kg/per day (Consumer, longtern	
Dermal	DNEL 62 mg/kg /per day (Consumer, longtern	
	DNEL 186 mg/kg /per day (Worker, longterm :	systemic)
Inhalative	DNEL 2420 mg/m3 (Worker, acute local)	
	DNEL 1210 mg/m3 (Worker, longterm system)	
	DNEL 200 mg/m3 (Consumer, longterm system	11C)
122.06.4	DNEL 60 mg/m3	
	-butyl acetate	
Oral	DNEL 2 mg/kg /per day (Consumer, longterm	
D1	DNEL 2 mg/kg /per day (Consumer, acute syst	
Dermal	DNEL 11 mg/kg /per day (Worker, longterm sy	
	DNEL 11 mg/kg /per day (Worker, acute system	
	DNEL 6 mg/kg/per day (Consumer, longterm	
Inhalatina	DNEL 6 mg/kg /per day (Consumer, acute syst	
Innaiaiive	DNEL 300 mg/m3 (Worker, longterm systemic)	,
	DNEL 600 mg/m3 (Worker, acute systemic) DNEL 300 mg/m3 (Worker, longterm local)	
	DNEL 600 mg/m3 (Worker, tongterm tocal) DNEL 600 mg/m3 (Worker, acute local)	
	DNEL 35.7 mg/m3 (Consumer, longterm system	mia)
	DNEL 30.7 mg/m3 (Consumer, tongterm system) DNEL 300 mg/m3 (Consumer; acute systemic)	
	DNEL 35.7 mg/m3 (Consumer, longterm local	
108-65-6 2	-methoxy-1-methylethyl acetate	'
Dermal	DNEL 796 mg/kg /per day (Worker, longterm :	systemic)
Dermai	DNEL 320 mg/kg/per day (Consumer, longter day)	
Inhalative	DNEL 275 mg/m3 (Worker, longterm systemic	
muanive	DNEL 33 mg/m3 (Consumer, longterm system)	
71-36-3 bu		9
0ral	DNEL 3.125 mg/kg /per day (Consumer, longt	erm systemic)
	DNEL 310 mg/m3 (Worker, longterm local)	
	DNEL 55 mg/m3 (Consumer, longterm local)	
PNECs	3 (11 / 15	
	etone	
67-64-1 ac	6 mg/l (Freshwater)	
67-64-1 ac PNEC 10	,	
PNEC 10.) mg/i iNeawaieri	
PNEC 10. PNEC 1.0	,	
PNEC 10. PNEC 1.0 PNEC 21	ng/l (Sporadic release)	
PNEC 10. PNEC 1.0 PNEC 21 PNEC 100	mg/l (Sporadic release) mg/l (Sewage treatment plant)	
PNEC 10. PNEC 1.0 PNEC 21 PNEC 100 PNEC 30.	ng/l (Sporadic release)	

— GI

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

	(Contd. of page
123-86	6-4 n-butyl acetate
PNEC	0.18 mg/l (Freshwater)
PNEC	0.018 mg/l (Seawater)
PNEC	0.36 mg/l (Sporadic release)
PNEC	35.6 mg/l (Sewage treatment plant)
PNEC	0.981 mg/kg (Freshwater sediment)
PNEC	0.0981 mg/kg (Seawater sediment)
PNEC	0.0903 mg/kg (Soil)
108-65	-6 2-methoxy-1-methylethyl acetate
PNEC	0.635 mg/l (Freshwater)
PNEC	0.064 mg/l (Seawater)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	3.29 mg/kg (Freshwater sediment)
PNEC	0.329 mg/kg (Seawater sediment)
PNEC	0.29 mg/kg (Soil)
71-36-	3 butan-1-ol
PNEC	0.082 mg/l (Freshwater)
PNEC	0.0082 mg/l (Seawater)
PNEC	2.25 mg/l (Sporadic release)
PNEC	2476 mg/l (Sewage treatment plant)
PNEC	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
DNEC	0.015 mg/kg (Soil)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

(Contd. on page 7)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

(Contd. of page 6)

Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: Different according to colouring

Odour: Solvent-like
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Melting point/freezing point:
Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.2 Vol % (123-86-4 n-butyl acetate)

· Upper: 13 Vol % (67-64-1 acetone) · Flash point: Not applicable, as aerosol.

· Auto-ignition temperature: 333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl

acetate)

Decomposition temperature:

• pH

Not determined.

Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

Density and/or relative density

Density at 20 °C (68 °F):

Relative density

Vapour density

0.8 g/cm³ (6.7 lbs/gal)

Not determined.

Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 85.9 %
· Water: 0.2 %
· VOC (EC) --674.4 g/l

· **VOC-EU%** 85.87 %

(Contd. on page 8)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

	(Contd. of pa
Solids content:	13.5 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard o	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
67-64-1 ac	etone	
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
123-86-4 n	ı-butyl aceta	nte
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)
108-65-6 2	-methoxy-1	-methylethyl acetate
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)
		(Contd. on page 9

(Contd. on page 9)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

(Contd. of page 8)

71-36-3 bu	ıtan-1-ol		(Contai or	1 8	
Oral	LD50	2292 mg/kg (rat)			
Dermal	LD50	3430 mg/kg (rabbit)			
Inhalative	LC50 / 4 h	17000 mg/m3 (rat)			

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.11 10.11.11.	12.1 1000000				
· Aquatic toxi	· Aquatic toxicity:				
67-64-1 acet	tone				
LC50/96h	8300 mg/l (fish)				
EC50/96h	7200 mg/l (algae)				
LC50 / 48 h	8450 mg/l (crustacean (water flea))				
108-65-6 2-1	108-65-6 2-methoxy-1-methylethyl acetate				
EC50 / 48 h	>500 mg/l (daphnia magna)				
LC50 / 96 h	LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)				
71-36-3 but	71-36-3 butan-1-ol				
LC50 / 96 h	LC50 / 96 h 1376 mg/l (fish)				
7779-90-0 tr	rizinc bis(orthophosphate)				
EC50 / 48 h	0.33 mg/l (crustaceans)				
LC50 / 96 h	0.37 mg/l (fish)				

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

(Contd. of page 9)

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
IMDG, IATA	
· Class · Label	2.1 Gases. 2.1
· 14.4 Packing group	2.1
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Code · Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2
· 14.7 Maritime transport in bulk according to IM instruments	10 Not applicable.
mon wheths	(Contd. on page 1

(Contd. on page 11)

Printing date 20.10.2023 Version number 111 (replaces version 110) Revision: 30.03.2022

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

		(Contd. of page 1
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	IL	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
	Code: E0	
	Not permitted as Excepted Quantity	
Transport category	2	
Tunnel restriction code	D	
· IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (\widetilde{EQ})	Code: E0	
1 1 (2)	Not permitted as Excepted Quantity	
	Code: E0	
	Not permitted as Excepted Quantity	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 12)

Version number 111 (replaces version 110) Revision: 30.03.2022 Printing date 20.10.2023

Trade name: WICKES ALL PURPOSE SPRAY PRIMER GREY 400 ML

(Contd. of page 11)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.