

Energy Efficiency Information				
Attribute	Symbol	Value		Units
Model identification		ECA60	EVA60, EVA70 & EVA90	
Annual Energy Consumption	$AEC_{Hood}$	45.2	45.2	kWh
Time increase factor	f	1.3	1.3	
Fluid Dynamic Efficiency	$FDE_{Hood}$	19.0	19.0	
Energy Efficiency Index	$EEl_{Hood}$	68.0 (B)	68.0 (B)	
Measured airflow at Best Efficiency Point	$Q_{BEP}$	186.5	186.5	m <sup>3</sup> /h
Measured Pressure at Best Efficiency Point	$P_{BEP}$	326	326	Pa
Maximum airflow	$Q_{MAX}$	350	350	m <sup>3</sup> /h
Measured electric power at Best Efficiency Point	$W_{BEP}$	89.0	89.0	W
Nominal lighting power	WL	4	4	W
Average illumination of the lighting system on the cooking surface	$E_{Middle}$	530	300	Lux
Measured power consumption in standby	$P_s$	--	0.7	W
Measured power consumption off mode	$P_o$	0	0.47	W
Sound power level	$L_{WA}$	64	64	dBA
Grease Filter Efficiency	$GFE_{Hood}$	37 (G)	37 (G)	%
Lamp Efficiency	$LE_{Hood}$	132.5 (A)	75 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.