## Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90



### **Optional accessories**

HEZ298105 Simmer plate
HEZ298108 Wok ring
HEZ298115 Small pot support

the desired cooking zones can be conveniently operated from the front.

The gas hob with front-mounted controls:

- Wok burner: powerful cooking at up to 3.3 kW
- Continuous cast-iron pan supports: for maximum stability.
- **Biomethane-ready**: your gas hob can also be powered with renewable biomethane gas.
- Ergonomic control knobs with raised center for precise adjustments.
- · Surface colour: elegant stainless-steel design.

### **Technical Data** Appliance type: ...... gas hob w integrated controls Installation type: .....Built-in Heating type: ......Gas Number of cooking zones: .....5 Type of control setting devices: ..... sword knobs Min. required niche size for installation (HxWxD): .....45 x 560-562 x 480-492 mm Dimensions: ...... 53 x 750 x 520 mm Dimensions of the packed product (HxWxD): ..... 145 x 793 x 597 mm Residual heat indicator: ...... without Color of surface: ...... Stainless steel Length of electrical supply cord: ......150.0 cm Frequency: ...... 50; 60 Hz





## Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90

# The gas hob with front-mounted controls: the desired cooking zones can be conveniently operated from the front.

#### Design

- Stainless steel surface
- Cast iron pan supports

## Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### **Burners and power**

- 5 gas burners:
- Left front: economy burner up to 1 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 3.3 KW (depending on gas type)
- Right rear: high-speed burner up to 3 KW (depending on gas type)
- Right front: standard burner up to 1.75 KW (depending on gas type)

#### Safety


- Flame failure safety device: prevents unwanted gas flow when flame goes out.

## Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm):  $53 \times 750 \times 520$
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 10.8 KW



## Series 4, Gas hob, 75 cm, Stainless steel PGQ7B5B90



\*\*\* With fitted oven underneath, possibly more see space requirements for the oven

measurements in mm

