



TimberTech Neo

Underlay

Heavyweight natural rubber underlay with **outstanding noise reduction.**

■ **Shhh! Underlay at work**

TimberTech Neo gives high insulation against impact sound – really bringing down noise levels and making the room a better place to be.

■ **Dry as a bone**

Silver vapour barrier film prevents moisture rising from the sub-floor – protecting your floor covering against damp.

■ **Old tyre, new life**

TimberTech Neo is made with rubber from recycled car tyres, which means old tyres don't go into landfill – so it's better for the planet.

Fitting Instructions

- Floor should be clean, dry, and dust-free.
- Roll out underlay silver side down in direction you'll lay floor covering.
- Butt up each roll flush to adjoining length and fit neatly around room edge. Use QA Vapour Tape on joints for added moisture protection.
- Use sharp knife or shears for clean cut.

Technical Data

Properties	Unit	Value	Method
Density	kg/m ³	400 ± 50	internal
Weight per square metre	kg/m ²	1.2 ± 10%	internal
Impact Sound Reduction	dB	≥ 23	BS EN ISO 717-2:2013 BS EN ISO 10140-3:2010
Thermal Resistance	Tog	0.72	BS4745:2005
Flammability (hot metal nut test)		Pass - low radius of effect*	BS 4790:1987 (2009)

*Values derived from similar products

The information given above may vary and is partly based on information from our suppliers. It represents the prevailing level of expertise and is not binding in a legal sense. The compliance of legal requirements lies within the customers own responsibility.

QA Flooring Solutions Ltd

Unit 2 Hurricane Drive

Liverpool L24 8RL

Tel: 0151 495 3434

Fax: 0151 427 0484

Email: sales@qaflooringsolutions.com

www.qaflooringsolutions.com

Heavy Traffic

Wood



Best for



Cushioning



Moisture Protection



Sound Reduction



Hard Wearing



Compression Recovery



Underfloor Heating



Hard Wearing



Heat Insulation



Commercial Use

Simply Better

Available in

Code QAU-TNE-01

Size 1m x 10m (10m²)

Thickness 3mm