



Lighting **excellence**



# Floodlight

150W IP65 Floodlight

Code: 4L2/1025

**Application** Commercial, Industrial



**Colour temperature**  
 Colour temperature describes the appearance, tint or hue of lighting.  
 Colour temperature is measured in kelvins and is marked by a figure followed by the letter "K".

2700K Warm White 3000K Warm White 3500K White 4000K Cool White 6000K Daylight

4lite | powered by WIZ | Make your spaces smarter.

## Product Features

- High specification IP65 rated floodlight for external applications
- Pre-wired with 1m cable
- Die-cast aluminium construction ensures durability and strength
- LED Lifetime L70 30,000

| Technical Information            |              |
|----------------------------------|--------------|
| Wattage                          | 150W         |
| Lumens Delivered                 | 18900lm      |
| Lm/W                             | 125lm/W      |
| Beam Angle                       | 90           |
| CRI                              | 82           |
| CCT                              | 4000K        |
| Input                            | 220/240V     |
| Operating Temp                   | -25°C - 40°C |
| SDCM                             | 6            |
| Product Weight without Packaging | 4.184 kg     |

| Technical Information |             |
|-----------------------|-------------|
| Light Source          | LED         |
| Colour / Finish       | Black       |
| IP Rating             | IP65        |
| Class Protection      | 1           |
| Internal / External   | External    |
| Mounting Option       | Wall        |
| Lumen Depreciation    | L70 50,000h |
| Warranty (Years)      | 5           |
| CE Mark               | Yes         |
| Height                | 350.7 mm    |

