

### PREMIUM PROTECTION FLEECE



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PFNB1	EACH	White	1m x 50m	1.5mm	2	12

#### Product Description:

This premium **product** has a slightly tacky fleece on the underneath and **film** on the top face. Ideal for covering of wooden and tiled stairs.

Supplied in rolls so easily transported and manoeuvred on site. Simply roll out, smooth into place and trim. Stays securely in place, does not require tape or additional fixing. Thick fibre layer creates excellent impact protection. Being 100% waterproof it holds spills and protects against wet foot traffic.

The breathable membrane allows moisture to evaporate whilst being liquid proof from the top. Breathability is 70gr/sqm/24hrs. When protecting hardwood floor or natural stone floors that require a high breathability please use Proguard Breathable Fleece Protection.

#### Benefits:

- Multi-surface protection - suitable for all surface types
- 100% waterproof
- Ideal for use on sensitive surfaces due to the soft material
- Flexible material - ideal for wrapping around awkward objects such as desks and balustrades
- Slightly self-adhesive
- Breathable to allow floors to cure

#### Limitations:

- We don't recommend this product to be used for heavily trafficked areas over long term projects. We recommend the Proguard Protectall Fleece for this application.
- Although this product has a level of anti-slip resistance this product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- If you require high breathability we recommend Proguard Breathable Fleece Protection.

#### Application:

Ensure surfaces onto which Proguard Premium Fleece is to be laid are free from loose rubble. Beginning from the corner of the room roll the fleece back towards you using Proguard Cloth Tape on any joints if required. The soft fleece should be laid face down. Use Proguard Low Tack PVC tape when adhering to sensitive surfaces such as marble and glass. To ensure a completely residue-free removal we recommend using Proguard Ultra Low Tack tape.

#### Performance Data:

Breathability	70gr/sqm/24hrs
Thickness	1.5mm