

Drybase® Flex Membrane

Product Description

A damp-proof and salt-resistant low-profile membrane for protection against moisture ingress in walls. The membrane is a 1 mm thick flexible polyethylene sheet and has polypropylene fleece layers laminated to both sides. The black fleece layer ensures good adhesion to the wall by means of Drybase® Flex Adhesive. The grey fleece layer ensures a strong bond to the plaster.

Benefits

- No need for plugs and drilling
- No unnecessary penetration of membrane
- Accepts plaster finish directly
- Flexible and versatile
- Watertight
- Fast application

Properties

Appearance	Membrane with black fleece one side and grey fleece on the other
Material	Polypropylene
Thickness	1.5 mm
Size(s) & Packaging	9.6 kg roll
Coverage	1 × 15 m
Salt Resistance	Excellent (salt bath testing conducted in lab conditions)
Tear Resistance	≥50 N
Storage	Dry conditions

Application Information

Preparation

Before **Drybase® Flex Membrane** can be applied, any structural defects on the substrate must be fixed. Clean the surface of the substrate to ensure maximum bonding of adhesive. Remove all surface laitance, loose particles, paint, etc. by means of wire brushing or light sandblasting.

Cut the membrane to the required area, making sure that there is a 25 mm gap between the floor and the membrane.



Application

Once the Drybase® Flex Adhesive has been applied to the wall, offer the **Drybase® Flex Membrane** up to the adhesive and use a trowel to apply gentle pressure spreading from the centre outwards. Ensure that full contact is established between the membrane and the adhesive.

After the adhesive has cured overnight, surface finishes can be applied such as gypsum based plaster, prior to a skim finish.

For detailed application instructions, refer to the full application guidelines which are available upon request from Safeguard.

Other Information

For health and safety information see the Safety Datasheet (available upon request).

Drybase® Flex Membrane is produced in accordance with ISO 9001 and ISO 14001 quality and environmental management systems.

Drybase® Flex Membrane is non-hazardous to the environment.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.