# Safety Data Sheet SUPER FLEXIBLE WHITE

Safety Data Sheet dated: 07/06/2022 - version 1



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: SUPER FLEXIBLE WHITE

Trade code: 9012029 UFI: HRH3-S0MV-3007-1CRP

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Cement based powder adhesive

Uses advised against: Data not available

#### 1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

## **SECTION 2: Hazards identification**





## 2.1. Classification of the substance or mixture

# Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1B May cause an allergic skin reaction. STOT SE 3 May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

# 2.2. Label elements

## Regulation (EC) n. 1272/2008 (CLP)

# **Pictograms and Signal Words**



Dange

# **Hazard statements:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.
H335 May cause respiratory irritation.

# **Precautionary statements:**

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains:

portland cement, Cr(VI) < 2 ppm

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 1 of 10

## Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$ .

Other Hazards: No other hazards

Prolonged exposition and/or intensive inhalation of respirable free crystalline silica (average diameter less than 10 micron in accordance with ACGIH) can cause pulmonary fibrosis commonly referred to as silicosis.

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not Relevant

#### 3.2. Mixtures

Mixture identification: SUPER FLEXIBLE WHITE

## Hazardous components within the meaning of the CLP regulation and related classification:

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

# 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 2 of 10

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

## 5.3. Advice for firefighters

Use suitable breathing apparatus.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

#### 6.4. Reference to other sections

See also section 8 and 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

# 7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# List of components with OEL value

	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Note
portland cement, Cr(VI) < 2 ppm CAS: 65997-15-1	National	FINLAND		1				FINLAND, respirabel fraktion
	NDS	POLAND		6				frakcja wdychalna
	NDS	POLAND		2				frakcja respirabilna
	SUVA	SWITZERLAND		5				A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory symptoms; asthma
	DFG	GERMANY		15				
	National	SPAIN		4.000				5 mg/m3 TWA (containing <1% of free Silica,

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 3 of 10

						free Silica, total dust)
	National	PORTUGAL		10		
	National	BELGIUM		10		
	National	HUNGARY		10		
	Malaysi a OEL	MALAYSIA		10.000		
	National	UNITED KINGDOM		10.000		inhalable dust
	National	UNITED KINGDOM		4.000		respirable dust
	National	CROATIA		10.000	10.000	
	DFG	GERMANY	С	15		
	ACGIH	AUSTRALIA		1.000		A4 - Not Classifiable as a
						Human Carcinogen; pulmonary function; respiratory symptoms; asthma
	Malaysi a OEL	MALAYSIA		10		5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)
	National	UNITED KINGDOM		10	30.000	5 mg/m3 TWA (containing <1% of free Silica, respirable dust);10 mg/m3 TWA (containing <1% of free Silica, total dust)
	National	UNITED KINGDOM		4.000		
	National	ROMANIA		10		
	ACGIH			1		A4 - Not Classifiable as a Human Carcinogen; pulmonary function; respiratory symptoms; asthma
	National	SPAIN		4		
	National	FINLAND		5		
	NDS	POLAND		6		
	National	LATVIA		6		
•	National	SWEDEN		0.100		SWEDEN, respirable aerosol
	National	NORWAY		0.100		K: Chemicals to be treated as carcinogenic.
	NDS	POLAND		2.000		frakcja wdychalna
	NDS	POLAND		0.300		frakcja respirabilna
	National	DENMARK		0.3	0.600	DENMARK, inhalable aerosol
	National	DENMARK		0.100	0.200	DENMARK, respirable aerosol
	ACGIH			0.025		(R), A2 - Pulm fibrosis, lung cancer
	EU			0.025		A2 (R) - Pulm fibrosis, lung cancer
	National	AUSTRIA		0.150		A*
	ACGIH			0.025		A2 - Suspected Human Carcinogen;lung

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 4 of 10

free crystalline silica (Ø <10  $\mu$ ) CAS: 14808-60-7

National SWEDEN	0.1		
National FRANCE	0.1		
National SPAIN	0.05		
National DENMARK	0.3		
National FINLAND	0.05		
National PORTUGAL	0.025		
National NORWAY	0.3	0.9	
National BELGIUM	0.1		
NDS POLAND	0.1		
NDS NETHERLANDS	0.075		
National CZECH REPUBLIC	0.1		
National HUNGARY	0.15		
Malaysi MALAYSIA a OEL	0.1		0.1 mg/m3 TWA (respirable dust)
National ESTONIA	0.1		
National SLOVAKIA	0.1	0.5	
National SLOVENIA	0.1		
National BULGARIA	0.07		
National ROMANIA	0.1		
National LITHUANIA	0.1		
National CROATIA	0.1		
National ITALY	0.100		

# 8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Nitrile gloves are suggested (1,3 mm; 480 min). Not recommended gloves: not waterproof gloves

#### Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

A dust mask (P2) should be worn if above exposure limits (EN 149)

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Solid Appearance: powder

Color: white

Odour: cement like

Odour threshold: Not available

Melting point / freezing point: Not available Initial boiling point and boiling range: Not available

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 5 of 10 Flammability: N.A.

Upper/lower flammability or explosive limits: Not available

Flash point: Not available

Auto-ignition temperature: Not available Decomposition temperature: Not available

pH: Not available

pH (water dispersion, 10%): 12.00

Viscosity: Not available

Kinematic viscosity: Not available Solubility in water: partly soluble

Solubility in oil: insoluble

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available Relative density: Not available Vapour density: Not available **Particle characteristics:** Particle size: Not available

#### 9.2. Other information

Miscibility: Not available Conductivity: Not available Explosive properties: == No other relevant information

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Stable under normal conditions

#### 10.2. Chemical stability

Stable under normal conditions

## 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

Stable under normal conditions.

# 10.5. Incompatible materials

None in particular.

#### 10.6. Hazardous decomposition products

None.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Contains cement. Cement gives a strong alkaline reaction with water and body fluids (e.g. sweat and eye fluids), therefore the contact with skin and eyes should be carefully avoided.

#### Toxicological information of the mixture:

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin Irrit. 2(H315) c) serious eye damage/irritation The product is classified: Eye Dam. 1(H318) d) respiratory or skin sensitisation The product is classified: Skin Sens. 1B(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure The product is classified: STOT SE 3(H335)

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 6 of 10

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties:**

No endocrine disruptor substances present in concentration >= 0.1%

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

Not classified for environmental hazards

Based on available data, the classification criteria are not met

## 12.2. Persistence and degradability

N.A

# 12.3. Bioaccumulative potential

NΑ

## 12.4. Mobility in soil

NΑ

#### 12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq$  0.1%.

## 12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

#### 12.7 Other adverse effects

Not available

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

## Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

#### **SECTION 14: Transport information**

Not classified as dangerous in the meaning of transport regulations.

# 14.1. UN number or ID number

Not Applicable

## 14.2. UN proper shipping name

Not Applicable

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 7 of 10

# 14.3. Transport hazard class(es)

Not Applicable

#### 14.4. Packing group

Not Applicable

#### 14.5. Environmental hazards

Not Applicable

# 14.6. Special precautions for user

Not Applicable

Road and Rail ( ADR-RID ):

Not Applicable

Air ( IATA ):

Not Applicable

Sea (IMDG):

Not Applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC): N.A. g/l

The product contains Cr (VI) under the limits established by annex. XVII pt.47. Respect the duration according to the information described on the packaging.

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

None

# Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: None.

Restrictions related to the substances contained: 75

# **SVHC Substances:**

SVHC substances not present in a concentration  $\geq 0.1\%$  (w/w)

#### German Water Hazard Class (WGK)

1

# 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

## **SECTION 16: Other information**

Code	Description		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 8 of 10

H318 Causes serious eye damage.H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

Code	Hazard class and hazard category	Description
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation Classification procedure (EC) Nr. 1272/2008

3.2/2 Calculation method
3.3/1 Calculation method
3.4.2/1B Calculation method
3.8/3 Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 9 of 10

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

Print date 09/06/2022 Production Name SUPER FLEXIBLE WHITE Page n. 10of 10