



Product Benefits & Features



Seamless integration

PerfectFit Sliding Hinge system makes for seamless dishwasher installation. It accommodates all niche machine heights and removes the need to cut the plinth. Fit for any modern kitchen.

- Auto off function
- Symbol panel
- TouchControl operation
- Delay Start: You can set the wash programme to start in up to 3 hours.
- Cutlery basket
- Water sensor
- Aqua control
- Electronic refill indicator for salt and rinse aid
- Manually height-adjustable upper basket
- Upper basket: 2 plastic, Foldable cup shelves
- Lower basket: Fixed tines
- Programmes: 90 Minutes, AUTO Sense, ECO, Machine Care, Quick 30 Minutes

Product Specification

Series	5000	Upper Spray Arm Type	Standard spray arm
Energy Rating	D	Lower Spray Arm Type	Standard
Number of Place Settings	13	Inlet Pipe Type	Aqua control
Dishwasher Programs	90 Minutes, AUTO Sense, ECO, Machine Care, Quick 30 Minutes Rinse aid, Salt, Buzzer, Delay start 3h, Drying phase, Program selected, XtraPower, Machine Care	Anti-flood Device Type	Floating switch
Push Button Functions		Product Number (PNC)	B - Open All
Drying System	AirDry Technology	Noise level, dB(A) (EU 2017/1369)	46
Noise Rating (dB)	C	Energy Consumption per 100 wash cycles (kWh)	84
Dimensions (mm) (HxWxD)	818x596x550	Culterly Basket	Yes
Built-in Dimensions (mm) (HxWxD)	820-900x600x550	Cutlery Drawer	None
Water Supply	Cold or hot		
Cord Length (m)	15		
Inlet Hose Length (cm)	150		
Outlet Hose Length (cm)	150		
Total Electricity Loading (W)	1950		
Wheels/Feet	2 adj feet + 1 front adj rear foot (adj 0 to 8cm)		
Voltage (V)	220-240		
Required Fuse (A)	10		
Frequency (Hz)	50		
Number of Programmes	5		
Number of Temperatures	2		
Door Colour	None		

