



Fluidmaster Technical Specification Data Sheet

Part Number: 6720-D-001




Product Description: Side Entry Water Saving Fill Airgap™ Valve

Applied Standard(s): BS 1212-4:2016

Material(s): ABS, Brass, EPDM, POM, PP, PVC

Approx. Weight (kg): 0.320

Product Dimensions: See Below





Fluidmaster Technical Specification Data Sheet

Product Details:

- Operating pressure Range - From 0.1bar to 10bar mains water pressure.
- Airgap distance built in design to meet AUK1 and AG airgap requirements.
- Meets requirements of the Water Supply (Water Fittings) Regulations, Byelaws in Scotland, as they apply to Type AG and Type AUK1 air gaps in WC suites and the interim agreement.
- Delay fill to help save water usage.
- BS1212-4 2016 Compliant.
- Reduces risk of water hammer.
- Quiet Filling - Noise level below 60dB (Normal Conversation 60-70dB).
- Pressure restrictor fitted to control flow rates when not using gravity systems- See instructions for details.
- Removable filtration - Filter fitted within thread.
- Small foot print allows for fitting into tight cisterns - Only protrudes 100mm into cistern.
- Normal Working Temperature – 0°C – 20°C.
- Inlet Thread – Plastic ½” BSP to suit tap connector.
- Made From Recyclable Materials.
- 100% Tested and Manufactured in Hereford, England, UK.
- For further information about Fluidmaster products please go to:

<https://www.fluidmaster.com/united-kingdom-products/>

Installation Notes: See installation instructions for full detail

End Of Life Data: Please recycle all components in accordance with local guidelines/facilities.

Product Warranty: 5 Years