

One Coat Everywhere Paint

RONSEAL®



Make decorating your whole home easier and quicker with Ronseal One Coat Everywhere. It'll give rich colour and tough protection to walls, ceilings, and pretty much anything else you want to paint. It's stain resistant and washable, ready to stand up to the challenges of everyday life.

One Coat Everywhere Paint's Key Benefits:

Tough and washable.

One paint for every room.

Grease, stain and mould resistant.

Quick drying.

TECHNICAL DATA

Colours Available in 21 colours in 2.5L and 7 colours in 5L

Number of Coats 1-2

Coverage 10m²/litre

Dry Time Touch dry in 1 hour, recoatable in 2-4 hours

Gloss/ Sheen Level 10-20 at 60°

Application-Temperature Above 10°C

Sizes 2.5L, 5L

STORAGE

Store in a cool, dry, well-ventilated place away from heat and sources of ignition. Carefully reseal partly used containers.

Always store and transport in a secure upright position to avoid spillage.

Protect from frost.

COVERAGE

Up to 10m²/litre

Coverage rate is dependent upon the type, nature and absorbency of the substrate.

ODOUR

Low VOC

PREPARATION

Make sure the room is above 10°C. Open your doors and windows and cover any areas you don't want to get paint on.

Previously painted walls: Sand off any loose or flaking paint. Then give the walls a wipe with a damp cloth. If painting over very bold or contrasting colour, use a basecoat first. Or you may need to put on an extra coat.

Bare Plaster: If you've had your walls and ceilings re-plastered, let it dry for 7 days before painting. You'll then need to seal the plaster. Use a basecoat or plaster sealer for this.

Bare and previously painted wood: Give the wood a light sand with 120 grit sandpaper, then wipe away the dust with a damp cloth. Fill any holes and cracks and treat any knots.

Bare and painted metal: Sand off any loose and flaking paint, then wipe away the dust with a damp cloth. *If you're painting ferrous metals, like steel or cast iron, you'll need to use a specialist metal primer first.

APPLICATION

With a Brush or Roller

Give your paint a good stir. If you've got more than one tin of the same colour, mix them together. This'll ensure the colour is consistent.

Get lots of paint on your roller or brush. Always work from dry to wet areas. Don't spread the paint too thin. Extra coats may be needed when trying to cover bold or contrasting colours.

It'll be touch dry in 1 hour. If a second coat is needed wait 2-4 hours.

Do not thin this paint.

COMPLETION

Wipe up spills immediately with a damp cloth. Allow at least 1 week for the paint to harden before washing it down.

Take as much paint off your brush or roller as you can. Wash in warm soapy water.

Don't empty leftover paint into drains or watercourses. Instead, contact your local authority, who may have particular ways to get rid of unused paint.

HEALTH AND SAFETY

Read carefully and follow all instructions. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Contains a biocidal product. Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. VOC content: EU limit for this product (Category (A/i) 140g/l (2010)). This product contains max 10 g/l VOC. Contains a biocidal product for preservation of the dry film against mould: 3-iodo-2-propynyl butylcarbamate.

Water-based paint. Ensure good ventilation during application and drying. When applying, it is advisable to wear eye protection.

Avoid inhalation of dust. Wear a face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SUPPL

Xavailable from decorators' merchants, hardware and D.I.Y. outlets, builders and timber merchants and garden centers

FLAMMABILITY

Non-flammable, flash point - closed cup >93°C.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

DISPOSAL

Don't empty leftover paint into drains or watercourses. Instead, contact your local authority, who may have a particular way to get rid of unused paint.

[Sherwin Williams has been registered to](#)
ISO14001:2015 (Registered Firm No. FM 1669/1).

Sherwin Williams operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.
Ronseal and 'Does exactly what it says on the tin' are registered trademarks of the Sherwin William's Company.
©2025

UK- Sherwin Williams UK limited
Avenue One, Station Lane, Whitney
Oxfordshire OX28 4XR
IRL – Sherwin Williams (Ireland) Ltd
Unit 53, Robinhood Industrial Estate,
Dublin 22, D22PW99.

Tel:
+44 (0)14 240 9469 (Technical Services)
+44 (00353) 1 2135760 (IRL)
E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk