

**Product Data Sheet**

**Application:** External Walls

# Isover Cavity Wall Slab (CWS) 32



## Thermal Insulation for External Masonry Cavity Walls

Isover Cavity Wall Slab (CWS) 32 is a glass mineral wool slab providing thermal performance in external masonry cavity walls. Manufactured with a water repellent binder, the strong, resilient and flexible slabs are 455mm wide to fit between standard wall tie spacing.

## Features and Benefits



**THERMAL  
INSULATION**

Thermal conductivity of 0.032 W/m.K. Helps to reduce heat loss within the building envelope and as a result decreases energy costs.



**RECYCLED  
GLASS**

Manufactured from up to 82% recycled glass with all electric equipment in the plant powered by 100% renewable electricity. For further details, see the Environmental section below or visit [isover.co.uk/CSR](http://isover.co.uk/CSR)



**A1 FIRE  
CLASSIFICATION**

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



**EASE  
OF INSTALL**

Slabs are 455mm wide to fit standard wall tie spacing for straightforward installation. No requirement for retaining discs when fully filling the cavity.

# Key Considerations

When using Isover Cavity Wall Slab (CWS) 32, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents which are available at [isover.co.uk/products/isover-cavity-wall-slab-cws-32](https://isover.co.uk/products/isover-cavity-wall-slab-cws-32) (product properties) and [isover.co.uk/healthandsafety](https://isover.co.uk/healthandsafety) (safety properties):

- BBA certificate
- Declaration of Performance
- Safe Use Instruction Sheet

## Product Specification

Product code	Thickness (mm)	Length (mm)	Width (mm)	Slabs per pack	Pack area (m <sup>2</sup> )	Packs per pallet	Pallet area (m <sup>2</sup> )	AD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m <sup>2</sup> .K/W)
5200625457	65	1200	455	12	6.55	15	98.28	0.032	2.00
5200625459	75	1200	455	10	5.46	15	81.90	0.032	2.30
5200625461	85	1200	455	8	4.37	15	65.52	0.032	2.65
5200625463	100	1200	455	6	3.28	15	49.14	0.032	3.10
5200619452	125	1200	455	5	2.73	15	40.95	0.032	3.90
5200619455	150	1200	455	4	2.18	15	32.76	0.032	4.65

## Characteristics

<b>Thermal</b>	Declared thermal conductivity of 0.032 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.	<b>Handling, Storage, Health and Safety</b>  Information regarding storage, installation and handling of Isover products and health & safety information can be found at <a href="https://isover.co.uk/healthandsafety">isover.co.uk/healthandsafety</a> . EUCB certified demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit <a href="https://isover.co.uk/accreditations">isover.co.uk/accreditations</a> ).
<b>Fire</b>	Euroclass A1 Reaction to Fire classification according to EN 13501-1.	
<b>Environmental</b>	All Isover products are manufactured under Environmental Management System – ISO 14001:2015.	
<b>Recycled Content</b>	Manufactured from up to 82% recycled glass.	
<b>Certification</b>	UKCA marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T4-WS. BBA Approved (Cert No:18/5560) for full fill and partial fill cavity walls, when installed, used and maintained as set out in the certification. Please visit <a href="https://isover.co.uk/BBA">isover.co.uk/BBA</a> to read the full certification for details and restrictions.	<b>Quality</b>  All Isover products are manufactured under Quality Management Standard – ISO 9001.



#### **Isover**

Saint-Gobain Isover UK Limited,  
Saint-Gobain House, East Leake, Loughborough,  
Leicestershire, LE12 6JU.

#### **Customer Service - Order Placement and Enquiries**

Tel: 0800 0322 555  
Email: [isover.customerservice@saint-gobain.com](mailto:isover.customerservice@saint-gobain.com)

#### **Technical Support Team**

Email: [isover.technical@saint-gobain.com](mailto:isover.technical@saint-gobain.com)

**[isover.co.uk](http://isover.co.uk)**

Published date: 10 July 2025

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [isover.co.uk](http://isover.co.uk)

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.