



AQUAPANEL® Joint Adhesive

AQUAPANEL® Joint Adhesive is used for wall applications to bond individual AQUAPANEL® Indoor boards.

Product-Data-Sheet



Areas of Application

Jointing between AQUAPANEL® Indoor Cement boards.

Compliance Standards

This product does not have a harmonised standard to allow for CE marking and or designated standard to allow for UKCA marking.

Key Benefits

- Product allows for quick and easy jointing of the AQUAPANEL® Indoor boards prior to applying a tiled finish
- Cleaner method as no mixing is required, resulting in less dust
- Quicker than traditional powdered options as no mixing required
- No on site water required for installation
- Does not contain any Diisocyanates

Build on us.

Creation Date: 21/11/2024
Revision Reference: 001
Revision Date: 21/11/2024

Performance Data

| Moisture Resistance (EN 12765) |
|--------------------------------|
| C4 |

Technical Information

| Colour | Volume (mL) | Coverage | Material Number |
|--------|-------------|--|-----------------|
| White | 290 | Approx. 50mL/m ² (approx. 25mL joint). Cartridge contents sufficient for: - Approx. 6.0 m ² (panel size 900 x 1200mm) - Approx. 9.0 m ² (panel size 1200 x 2400mm) | 842864 |

Sustainability

Recyclability

Not recyclable.

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no VOCs. For more information please consult the Safety Data Sheet.

Storage and Handling

Store in a cool and dry area (between +5°C and +25°C) in sealed original container.

The material, ambient and background temperature must not fall below +5°C.

To avoid allergy risks, we recommend working with gloves or protecting the hands with a protective cream.

Packaging

Plastic Cartridge with nozzle.

Shelf Life/Service Life

Unopened storage life 15 months after production. See back of tube for manufacturing date.

Disposal & Repair

Disposal should be in accordance with local authority requirements.

Health & Safety

Please follow the instructions on the safety data sheet, there are no legal precautions.

Application / Installation

Working time: Approx. 15 minutes/m².

Before applying the AQUAPANEL® Joint Adhesive, ensure that the edges are cleaned using a wet brush. This ensures the best adhesion to the board.

Apply a continuous linear bead of AQUAPANEL® Joint Adhesive to the clean edge of the already-fixed AQUAPANEL® Cement Board Indoor.

Place the next board onto the substructure and press against the joint adhesive (joint width approx. 1mm) and screw the board into place.

This must be done before the next panel is placed. Additional filling of the joint should not be done.

Remove excess before the product sets fully (normally within 2-4hrs)

Additional Documentation

[Safety Data Sheet](#)

Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)
Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 18/12/2024
Revision Reference: 001
Revision Date: 18/12/2024