



TECH SHEET

SOIL & WASTE SYSTEM

21.5mm OVERFLOW WASTE

A 21.5mm Solvent Weld Overflow System in PVC-U with an extensive range of fittings to meet most installation requirements. Available in White (RAL9003) and Black (RAL9005).



FIXING GUIDE

- Fix pipe brackets at maximum 0.5m centres for both vertical and horizontal runs.
- No expansion gap required
- Solvent weld joints to be welded with FloPlast Solvent Cement.

WORKING TEMPERATURES

The FloPlast Overflow Waste System may be used to carry liquids when subjected to a continuous flow, with a maximum temperature of 76° c.

Intermittent discharges of up to 100°c may occur, provided that a duration of less than two minutes is observed



SOIL & WASTE SYSTEM

21.5mm OVERFLOW WASTE

Product	Colours	Code
Overflow Pipe - 3m		
	B W	OS01
Straight Coupling		
	B W	OS10
Bend 90°		
	B W	OS11
Bend 135° (45°)		
	B W	OS12
Tee		
	B W	OS13
Straight Tank Connector		
	B W	OS14
Bent Tank Connector		
	B W	OS15
Pipe Clip		
	B W	OS16
Overflow Waste 32mm Reducer		
	B W	OS17
Fits into a socket of both push-fit and solvent weld systems.		
Overflow Waste 42mm Reducer		
	B W	OS18
Fits into a socket of both push-fit and solvent weld systems.		

SYSTEM FEATURES



Overflow waste reducer (32mm & 40mm) will connect to both solvent weld and push fit waste sockets.



Components have a consistent high gloss finish and colour and are essentially maintenance free.



Tough and durable material, yet lightweight for ease of installation