




CLASSIC PLUS


1 200 x 190 x 8 mm
1 box = 10 planks = 2,280 m²



uniclic[®]
PATENTED TECHNOLOGY

UK CA	UNILIN BV, division flooring, Ooigemstraat 3, B-8710 Wielsbeke, Belgium
24	
EN 14041:2004 / AC:2006	AB8515 DOP: QSLMPUK0501
Floorcovering with surface layer based on amino resins for indoor use in buildings according to manufacturer's specifications.	
Essential characteristics	Performance/Class
Reaction to Fire Class	Cfl-s1
Content of PCP	<0,1%
Slipperiness	Class DS
Emission of formaldehyde	Class E1
Electrical behaviour	Antistatic
Thermal conductivity	λ=0,12W/mK

CE	UNILIN BV, division flooring, Ooigemstraat 3, B-8710 Wielsbeke, Belgium
24	
EN 14041:2004 / AC:2006	NB0493 DOP: QSLMP0501
Floorcovering with surface layer based on amino resins for indoor use in buildings according to manufacturer's specifications.	
Essential characteristics	Performance/Class
Reaction to Fire Class	Cfl-s1
Content of PCP	<0,1%
Slipperiness	Class DS
Emission of formaldehyde	Class E1
Electrical behaviour	Antistatic
Thermal conductivity	λ=0,12W/mK

Additional Information	
EN 13329	
7 - 14 mm	
Installation instructions & warranty conditions: see quickstep.com	
Store and transport in dry conditions	

For more information about covered patents go to unilintechnologies.com/en/mohawk

Quick-Step is a quality product produced by Unilin BV, division flooring, Ooigemstraat 3, B-8710 Wielsbeke, Belgium.

Contact us via <https://www.unilin.com/en/contact>

a brand of **UNILIN**

Importer in UK is Unilin Flooring UK & Ireland, Unit 6 Ballinacraig Business Park, Greenbank, Industrial Estate, Newry, BT34 2QX, Northern Ireland.

WARNING: Drilling, sawing, sanding or machining wood products can expose you to wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection. For more information go to www.P65Warnings.ca.gov/wood



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



FR **TRIEZ RÉEMPLOYEZ RECYCLEZ**



Adresses sur quefairedemesdechets.fr



SCAN



COVQSCLAP8401

025571 01

FOR EASY INSTALLATION INSTRUCTIONS OR GO TO QUICKSTEP.COM