

Technical Data Sheet	Title: 0146 Soundproof PE Foam	
Effective Date: Apr 2025	Prepared By: Sam Murphy	
Issue Number: 1	Authorised By: Craig Laing	

Product Description

No liner Grey PET laminated single sided closed cell PE foam coated with acrylic adhesive.
(Acoustic/Batten tape).

Applications

Designed to be used within walls, ceilings, floors, timber, composite or metal systems as anti-rattle & acoustic reduction applications.

Features & Benefits

Anti-squeak
Reduce noise and vibrations
Very good initial tack
Great ageing & weathering properties

Technical Performance

Description	Units	Value	Test Method
Temperature Range	°c	+60 constant -10 low	-
Thickness	mm	3	GB/T7125-2014
Loop tack	N/25mm	16	GB/T31125-2014

REACH SVHC Status

NO SVHC present according to candidates list of the **UK 25/06/20** & **EU 12/01/25**

RoHS 1 2&3 Compliance Status

(RoHS1) Directive 2002/95/EC & (RoHS2) 2011/65/EU amending Annex II to Directive (RoHS3) EU 2015/863 of the European Parliament and of the Council as regards the list of restricted substances.

Storage Details

Store at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)