PSB015F3000

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	PSB015
Product Range	Plasterers Accessories
Product Sub-range	uPVC Multi-coat beads - Internal or External Use
Product Type	Stop Bead

Material	uPVC
Coating/Finish/Colour	White
Length 1/Projection	3000mm
Width/Wing Length	45mm Wing length
Plaster/Render/Joist depth	15mm Render/Plaster
Material Gauge	~1mm (Varies)
Individual Weight (kg)	0.606
Fixing Type	Clout Nails/ Screws+Washers/Render dabs/External Grab Adhesive
Installation requirement 1	Fix at intervals not exceeding 600mm
Installation requirement 2	Avoid damage to beads when trowelling. Do not use abrasives to clean beads.
Installation requirement 3	Cut using a hacksaw
Unit of Sale EAN	5014316002967
Sales Qty	25
Packaging material	Polythene
Packaging weight	0
Packaged transit weight	15.15
Features/Benefits 1	Suitable for all render/plaster types and exposure classes
Features/Benefits 2	Provides a straight edge and protects plaster/render edges from damage
Features/Benefits 4	White finish
Options 1	None

HEALTH AND SAFETY INFORMATION

1. Identification
‘Expamet’
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition
uPVC

3. Hazards Identification
Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures
Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures
Non?flammable material.

6. Accidental release measures
Not applicable.

7. Handling and storage
Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8.Exposure controls
Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties
Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity
Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information
High temperatures can produce fumes.

12. Ecological information
No known Hazard.

13. Disposal considerations
Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information
Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.