
PFB001F2500

GALLERY



PRODUCT ATTRIBUTES

Brand	Expamet
Generic Ref	PFB001
Product Range	Plasterers Accessories
Product Sub-range	Skim-coat plaster beads - Internal UseSkim-coat plaster beads - Internal Use
Product Type	Flexible arch bead
Material	uPVC
Coating/Finish/Colour	White
Length 1/Projection	2500mm

Width/Wing Length	25mm Wing length
Plaster/Render/Joist depth	2mm Skim
Material Gauge	1mm
Individual Weight (kg)	0.163
Fixing Type	Galvanized Clout Nails/Staples/Grab Adhesive/Plaster
Installation requirement 1	Fix at intervals not exceeding 600mm
Installation requirement 2	Avoid damage to beads when trowelling.
Unit of Sale EAN	5014316007559
Sales Qty	25
Packaging material	Polythene
Packaging weight	0
Packaged transit weight	4.075
Features/Benefits 1	Can be bent to 200mm radius in one plane
Features/Benefits 2	Perforated wing provides a key to prevent cracking
Features/Benefits 3	Provides a clean straight corner and protects plaster edges from damage
Features/Benefits 4	Can easily be cut to size using a hacksaw/tin snips
Options 1	None

HEALTH AND SAFETY INFORMATION

1. Identification
‘Expamet’
Birtley Group Ltd
Mary Ave,
Birtley,
DH3 1JF
UNITED KINGDOM
(0191) 410 6631

2. Composition
uPVC

3. Hazards Identification
Possible cuts from sharp steel edges.
Toxic and irritant fumes from high temperatures

4. First aid measures
Skin and eye contact: Treat cuts from steel edges as required.
Ingestion: Not applicable.
Inhalation: Remove from source of fumes and dust.

5. Fire fighting measures
Non?flammable material.

6. Accidental release measures
Not applicable.

7. Handling and storage
Bands and straps must not be used for lifting.
Use suitable PPE when handling products.
Assess manual handling risks before lifting.
Products should be stacked on firm level ground in dry conditions.

8.Exposure controls
Wear personal protection such as gloves and safety goggles when handling products.
Some products may have a film of soluble cutting fluid after manufacture; therefore carry out personal hygiene including proper washing of hands, after contact.

9. Physical and chemical properties
Products are supplied in various lengths, widths and gauges.
Metallic grey appearance.

10. Stability and reactivity
Products are stable under normal conditions but if subjected to high temperatures, fumes are produced.

11. Toxicological information
High temperatures can produce fumes.

12. Ecological information
No known Hazard.

13. Disposal considerations
Recycle or dispose of in accordance with Waste Management Licensing Regulations.

14. Transport information
Not classified as hazardous for transport.

15. Regulatory information

Products are articles and have no registration obligation under REACH.

16. Other information

All products must be installed in accordance with Expamet Building Products' published instructions.

Where structural products are to be removed from an existing installation, care must be taken to ensure that the procedure followed does not compromise the loading/installation restrictions applicable to the products.

Actual fixing installations must comply with current Health and Safety requirements.