

7. HANDLING AND STORAGE

Store in sealed containers in a cool, dry, well ventilated area, away from sources of heat or ignition. Keep in original containers. Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Controls: See Section 2 for Occupational Exposure Limits (OEL).

Precautionary Measures: Keep away from all sources of ignition. Do not smoke. Keep containers closed when not in use. Use only in well ventilated areas. Avoid contact with skin and eyes. Wash hands after work and before breaks.

Respiratory Protection: Wear approved HSE respiratory protective equipment for organic vapours if exposure levels are above the occupational exposure limits.

Eye Protection: Wear approved safety glasses or goggles to BS 2902.

Hand/Skin Protection: Wear solvent resistant gloves (e.g. nitrile rubber or polyethylene) and protective clothing. Barrier creams are beneficial in cleaning any bitumen from the skin. Wash hands thoroughly before eating or drinking. Contaminated clothes should be laundered before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Brushable liquid
Colour: Black
Odour: Hydrocarbon solvent
Flash point: 37°C (Method: Closed Cup)

10. STABILITY AND REACTIVITY

Stable under recommended handling and storage conditions.

11. TOXICOLOGICAL INFORMATION

Inhalation: Exposure to substances above their occupational exposure limits may result in drowsiness and adverse health effects.

Eyes: May cause moderate irritation, discomfort possible damage.

Skin: Prolonged or repeated contact with skin may result in irreversible effects.

Ingestion: May cause irritation to the mouth and respiratory system. May cause nausea and general discomfort.

12. ECOLOGICAL INFORMATION

The product should not be allowed to enter drains or watercourses and should not be deposited where it can affect ground or surface water. In liquid state it likely to be moderately toxic aquatic organisms. In dry state it is not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with national and local regulations. Keep out of reach of children.

Waste, including emptied containers, should be disposed of in accordance with the Controlled Waste Regulations 1992 and the general requirements of the Control of Pollution Act 1974 and the Environmental Protection Act 1990.

14. TRANSPORT INFORMATION

Product Name:	Wickes Easy Seal S.A. Primer		
Proper Shipping Name:	Paint		
UN No:	1263	UN Packing Group:	III
Hazard Class:	3	Hazard Label (for Carriage):	Flammable liquid
Road/Rail (ADR/RID)			
ADR/RID UN No:	1263	ADR/RID Item No:	31(c)
ADR/RID Hazard Class:	3	ADR/RID Hazard Label:	Flammable liquid
Tremcard:	30 G 80		
Sea (IMO)			
IMDG UN No:	1263	Marine Pollutant:	Yes
IMDG Hazard Class:	3.3	IMDG Hazard Label:	Flammable liquid
IMDG Page No:	3372	IMDG Packing Group:	III
IMDG EmS No:	3-05	IMDG MFAG Table No:	310, 313
Air (ICAO)			
ICAO UN No:	1263	ICAO Packing Group:	III
ICAO Hazard Class:	3	ICAO Hazard Label:	Flammable liquid

15. REGULATORY INFORMATION

Product Name:	Wickes Easy Seal S.A. Primer Contains xylene	
CHIP indication of danger with associated symbol:	HARMFUL Diagonal Cross	DANGEROUS FOR THE ENVIRONMENT Dead Tree and Fish
Risk phrases:	Flammable (R10) Harmful by inhalation (R20) Irritating to skin (R38) Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R51/53)	
Safety phrases:	Wear suitable protective clothing and gloves (S36/37) Do not breathe vapour (S23) Use only in well ventilated areas (S51) Dispose of this material and its container to hazardous or special waste collection point (S56) If swallowed, seek medical advice immediately and show this container or label (S46) Keep out of reach of children (S2)	
Other phrases: (Not on warning label)	Keep away from sources of ignition- No Smoking (S16) Avoid contact with skin and eyes (S24/25)	

16. OTHER INFORMATION

Reference Sources: REF 1 - CONCAWE Report No. 85/87 REF 2 - HSE Guidance Notes EH40

Revision Comments: This issue replaces RSDS 05W, Revision Issue No.3 : November 2000..
Section amended: 1, 16.

For further information contact Ruberoid Technical Services Department: -
Cawdor Quarry, Matlock, Derbyshire, DE4 2JH – Tel: 0800 783 3210 Fax: 01629 583375 Email: apd.tech@permanite.com
Web Site: www.ruberoid.co.uk
In an emergency, telephone 01629 582213.

REVISION ISSUE No.4 : JANUARY 2005

The information contained in this data sheet does not constitute an assessment of workplace risk as required by current legislation. Whilst every care is taken to see that the information is correct and up to date, it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.