

## DECLARATION OF PERFORMANCE

**Factory Control Certificate Number: 0086-CPD-537586**

**1. Product Group:**

**Group 15** – Roofing membranes with a polyester carrier, APP modified with granule surfacing and a sacrificial plastic film backing

**2. Unique Product Names / Codes**

Product name	Unique Identification Code	Nominal weight	Nominal dimensions
Adesso Cap Sheet Green	62200108	4.12 kg/m <sup>2</sup>	8 x 1m
Adesso Cap Sheet Brown	62300208	4.12 kg/m <sup>2</sup>	8 x 1m
Adesso Cap Sheet Black	62400308	4.12 kg/m <sup>2</sup>	8 x 1m
Permatorch Cap Sheet Green	62250108	4.75 kg/m <sup>2</sup>	8 x 1m
Permatorch Cap Sheet Brown	62350208	5.0 kg/m <sup>2</sup>	8 x 1m
Permatorch Cap Sheet Black	62450308	5.0 kg/m <sup>2</sup>	8 x 1m
IKO APP Polyester Cap Sheet Green	62270108	4.25 kg/m <sup>2</sup>	8 x 1m

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Hot applied for use in multi-layer systems by torching

**4. Manufacturer:** IKO PLC  
 Appley Lane North  
 Appley Bridge  
 Wigan  
 Lancashire  
 WN6 9AB

**5. Authorised Representative:** Not Applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:**

2+

**7. Harmonised standard:** EN 13707:2004 +A2:2009

**8. Notified Body:** BSi

**9. Declared Performance:**

Essential Characteristic	Performance	Harmonised Technical Specification
External fire performance	F <sub>ROOF</sub> (t4)	EN 13501-5
Reaction to fire	F	EN 13501-1
Watertightness	Pass	EN 1928

Maximum tensile force	Long $\geq$ 550 N/50mm Tran $\geq$ 400 N/50mm	EN 12311-1
Elongation	Long $\geq$ 30% Tran $\geq$ 30%	EN 12311-1
Resistance to tearing	Long $\geq$ 200N Tran $\geq$ 200N	EN 12310-1
Flexibility at low temperature	Upper $\leq$ -10°C Lower $\leq$ -10°C	EN 1109

Signed for and on behalf of the manufacturer by:



Terry Edwards  
R&D and Quality Manager  
Wigan, July 2013

---