

## **Declaration of Performance**

## Therma™ TP10

1000/1001.CPR.2013.TP10.002

Unique identification code of the product-type: Therma™ TP10

Intended use/es: Thermal insulation for buildings

Manufacturer: Kingspan Insulation Ltd, Herefordshire HR6 9LA,UK

System/s of AVCP: System 3

Harmonised technical specification: BS-EN 13165:2012+A1:2015

Notified body/ies: FIW München NB. 0751 University of Salford NB 1145.Exova NB 1104

Essential characteristics		Performance
Thermal resistance	Thermal resistance R <sub>D</sub> ((m².K)/W)	d <sub>N</sub> 30mm     1.35       d <sub>N</sub> 40mm     1.80       d <sub>N</sub> 50mm     2.25       d <sub>N</sub> 60mm     2.70       d <sub>N</sub> 70mm     3.15       d <sub>N</sub> 80mm     3.60       d <sub>N</sub> 90mm     4.05       d <sub>N</sub> 100mm     4.50       d <sub>N</sub> 120mm     5.45       d <sub>N</sub> 130mm     5.90       d <sub>N</sub> 140mm     6.35       d <sub>N</sub> 150mm     6.80       d <sub>N</sub> 160mm     7.25
	Thermal conductivity $\lambda_D$ (W/(m.K))	0.022
	Thickness tolerance	d <sub>N</sub> 25-200mm T2
Reaction to fire		D,s2,d0
Durability of reaction to fire against heat, weathering, ageing / degradation		Reaction to fire does not change with time
Dimensional stability under specified temperature and humidity condition		DS(70,90)3 DS(-20,-)1
Deformation under specified compressive load and temperature conditions		DLT(2)5
Compressive strength	Compressive stress or compressive strength	CS(10\Y)140
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
	Short term water absorption	NPD
Water permeability	Long term water absorption Flatness after one sided wetting	NPD NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Release of dangerous substances to the indoor environment		No harmonized test method available
Continuous glowing combustion		No harmonized test method available
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Richard Burnley

Managing Director UK and Ireland 1/1/2016

Keil