according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WICKES ONE COAT GLOSS SOLVENT BASED

Further trade names

W702730002 WICKES One Coat Gloss PBW 0.750L

Abbreviation: 3001

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

solvent based coating material

1.3. Details of the supplier of the safety data sheet

Company name: Wickes Building Supplies Limited

Lodge Way House Harlestone Road

Street: Harlestone Road
Place: NN5 7UG Northampton

Telephone: 0844 892 2701

e-mail: safetydatasheet@jwo.com

Contact person: Customer Service Telephone: 0844 892 2701

Internet: www.wickes.co.uk

Responsible Department: GBK GmbH - Global Regulatory Compliance - Emergency-Nr +49(0)6132-84463

1.4. Emergency telephone +49 (0)6132-84463

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard Statements:

Flammable liquid and vapour.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403 Store in a well-ventilated place.

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 2 of 8

P501 Dispose of contents/container to in line with your local waste disposal regulations..

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains ethyl methyl ketoxime. May produce an allergic reaction.

Additional advice on labelling

The classification was made according to the calculation procedure of Regulation (EC) No 1272/2008.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alkyd resin lacquer in hydrocarbons

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
64742-48-9	Naphtha (Erdöl).			25 - 50 %	
	265-150-3				
	Asp. Tox. 1; H304				
96-29-7	2-Butanonoxim				
	202-496-6	616-014-00-0			
	Carc. 2, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1; H351 H312 H318 H317				

Full text of H and EUH statements; see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Treat subsequently with skin cream.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids.

If eye irritation persists, consult a specialist.

After ingestion

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

Do not induce vomiting.

Summon a doctor immediately.

SECTION 5: Firefighting measures

5.1. Extinguishing media

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 3 of 8

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Carbon monoxide and carbon dioxide.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges (earthing (grounding) at pouring).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 4 of 8

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles.

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Butyl latex, 0,7 mm, 480 min., i.e. protective glove made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing.

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of high concentrations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid - viscous
Colour: Different
Odour: Characteristic

Test method

pH-Value: (n.a. = not applicable; n.d. = not

determined)

Changes in the physical state

Melting point: (n.a. = not applicable; n.d. = not

determined)

Initial boiling point and boiling range: (n.a. = not applicable; n.d. = not

determined)

Sublimation point: (n.a. = not applicable; n.d. = not

determined)

Softening point: (n.a. = not applicable; n.d. = not

determined)

Pour point: (n.a. = not applicable; n.d. = not

determined)

Flash point: 23-60 °C

Flammability

Solid: (n.a. = not applicable; n.d. = not determined)

Gas: (n.a. = not applicable; n.d. = not determined)

Lower explosion limits: (n.a. = not applicable; n.d. = not

determined)

Upper explosion limits: (n.a. = not applicable; n.d. = not

determined)

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED						
Print date: 09.09.2015	Product code: W702730-W004	Page 5 of 8				
Ignition temperature:	(n.a. = not applicable; n.d. = not determined)					
Auto-ignition temperature						
Solid:	(n.a. = not applicable; n.d. = not determined)					
Gas:	(n.a. = not applicable; n.d. = not determined)					
Decomposition temperature:	(n.a. = not applicable; n.d. = not determined)					
Vapour pressure:	(n.a. = not applicable; n.d. = not determined)					
Vapour pressure:	(n.a. = not applicable; n.d. = not determined)					
Density:	0,93-1,29 g/cm³					
Bulk density:	(n.a. = not applicable; n.d. = not determined)					
Water solubility: (at 20 °C)	Immiscible					
Partition coefficient:	(n.a. = not applicable; n.d. = not determined)					
Viscosity / dynamic:	(n.a. = not applicable; n.d. = not determined)					
Viscosity / kinematic:	(n.a. = not applicable; n.d. = not determined)					
Flow time:	> 30 s	3 DIN EN ISO 2431				
Vapour density:	(n.a. = not applicable; n.d. = not determined)					
Evaporation rate:	(n.a. = not applicable; n.d. = not determined)					

< 50 %

Solvent content: **9.2. Other information**

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapours may form explosive mixture with air.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Further information

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 6 of 8

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
96-29-7	2-Butanonoxim				
	dermal	ATE	1100 mg/kg		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Sensibilisierung Haut Bemerkung: No sensitization responses were observed.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Observations relevant to classification

The product causes burns of eyes, skin and the mucous membranes.

Components of the product may be absorbed into the body through the skin.

Further information

Repeated or prolonged exposure may cause irritation of eyes and skin.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
96-29-7	2-Butanonoxim					
	Acute crustacea toxicity	EC50	750 mg/l	48 h	Daphnia magna	

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
96-29-7	2-Butanonoxim	0,63

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

Hazardous water pollutant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 7 of 8

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Old paints, uncured

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances

Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 126314.2. UN proper shipping name:FARBE14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Hazard No: 30

Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 I (subsection 2.2.3.1.5 ADR).

Marine transport (IMDG)

14.1. UN number:UN 126314.2. UN proper shipping name:PAINT14.3. Transport hazard class(es):314.4. Packing group:IIIMarine pollutant:NoEmS:F-E; S-E

Air transport (ICAO)

14.1. UN number:UN 126314.2. UN proper shipping name:PAINT14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Other applicable information (air transport)

PAC 309 (60 L), CAC 310 (220 L)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No 1907/2006

WICKES ONE COAT GLOSS SOLVENT BASED

Print date: 09.09.2015 Product code: W702730-W004 Page 8 of 8

EU regulatory information

2004/42/EC (VOC): 2004/42/EG A/d 300 (2010) max. 300 g/l VOC

National regulatory information

Water contaminating class (D): 2 - water contaminating

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
------	------------------------------

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains ethyl methyl ketoxime. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)