

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WICKES QUICK DRY SATIN WATER BASED

Further trade names

W702738002	WICKES Quick Dry Satin PBW	0,750L
W702738605	WICKES Quick Dry Satin Black	0,750L
W702739002	WICKES Quick Dry Satin PBW	2,500L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

water based emulsion

1.3. Details of the supplier of the safety data sheet

Company name:	Wickes Building Supplies Limited	
	Lodge Way House	
Street:	Harlestone Road	
Place:	NN5 7UG Northampton	
Telephone:	0844 892 2701	
e-mail:	safetydatasheet@jwo.com	
Contact person:	Customer Service	Telephone: 0844 892 2701
Internet:	www.wickes.co.uk	
Responsible Department:	GBK GmbH - Global Regulatory Compliance - Emergency-Nr +49(0)6132-84463	

1.4. Emergency telephone number:

+49 (0)6132-84463

SECTION 2: Hazards identification

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH208 Contains benz/methyl/chlormethyl-isothiazolon. May produce an allergic reaction.

Additional advice on labelling

No hazardous substance or mixture according to Regulation (EC) No 1272/2008. Not classified as dangerous according to directive 1999/45/EC.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

water based emulsion for walls and ceilings

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 2 of 6

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids.
If eye irritation persists, consult a specialist.

After ingestion

Immediately give plenty of water (if possible charcoal slurry).
If you feel unwell, seek medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product itself does not burn.
Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

Carbon monoxide and carbon dioxide.
Nitrogen gases (NOx)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Additional information

Cool containers at risk with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Avoid contact with the skin and the eyes.
Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 3 of 6

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Safety goggles with side protection.

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Butyl latex, 0,7 mm, 480 min., 60 min., i.e. protective glove made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Respiratory protection

No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid - viscous
Colour:	white
Odour:	Characteristic

pH-Value (at 20 °C):	8,5-9,5	Test method
----------------------	---------	--------------------

Changes in the physical state

Melting point:	(n.a. = not applicable; n.d. = not determined)
----------------	--

Initial boiling point and boiling range:	100 °C
--	--------

Sublimation point:	(n.a. = not applicable; n.d. = not determined)
--------------------	--

Softening point:	(n.a. = not applicable; n.d. = not determined)
------------------	--

Pour point:	(n.a. = not applicable; n.d. = not determined)
-------------	--

Flash point:	nicht anwenbar
--------------	----------------

Flammability

Solid:	(n.a. = not applicable; n.d. = not determined)
--------	--

Gas:	(n.a. = not applicable; n.d. = not determined)
------	--

Lower explosion limits:	(n.a. = not applicable; n.d. = not determined)
-------------------------	--

Upper explosion limits:	(n.a. = not applicable; n.d. = not determined)
-------------------------	--

Ignition temperature:	(n.a. = not applicable; n.d. = not determined)
-----------------------	--

Auto-ignition temperature

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 4 of 6

Solid:	(n.a. = not applicable; n.d. = not determined)
Gas:	(n.a. = not applicable; n.d. = not determined)
Decomposition temperature:	(n.a. = not applicable; n.d. = not determined)
Vapour pressure: (at 20 °C)	ca. 23 hPa
Vapour pressure:	(n.a. = not applicable; n.d. = not determined)
Density (at 20 °C):	1,2-1,25 g/cm ³
Bulk density:	(n.a. = not applicable; n.d. = not determined)
Water solubility: (at 20 °C)	Completely miscible
Viscosity / dynamic:	(n.a. = not applicable; n.d. = not determined)
Viscosity / kinematic:	(n.a. = not applicable; n.d. = not determined)
Flow time: (at 20 °C)	80-120 s 6 DIN EN ISO 2431
Vapour density:	(n.a. = not applicable; n.d. = not determined)
Evaporation rate:	(n.a. = not applicable; n.d. = not determined)
Solvent separation test:	(n.a. = not applicable; n.d. = not determined)
Solvent content:	(n.a. = not applicable; n.d. = not determined)

9.2. Other information

Festkörper: 44,00-50,00 %

SECTION 10: Stability and reactivity**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.

10.6. Hazardous decomposition productsNitrous gases
Carbon monoxide and carbon dioxide.**Further information**

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

(n.a. = not applicable; n.d. = not determined)

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 5 of 6

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience**Observations relevant to classification**

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

SECTION 12: Ecological information

12.1. Toxicity

(n.a. = not applicable; n.d. = not determined)

12.2. Persistence and degradability

(n.a. = not applicable; n.d. = not determined)

12.3. Bioaccumulative potential

(n.a. = not applicable; n.d. = not determined)

12.4. Mobility in soil

(n.a. = not applicable; n.d. = not determined)

12.5. Results of PBT and vPvB assessment

(n.a. = not applicable; n.d. = not determined)

12.6. Other adverse effects

(n.a. = not applicable; n.d. = not determined)

Further information

Ecological injuries are not known or expected under normal use.

Do not flush into surface water or sanitary sewer system.

Low hazard to waters.

SECTION 13: Disposal considerations

13.1. Waste treatment methods**Advice on disposal**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Old paints, uncured

Waste disposal number of used product

080120 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

WICKES QUICK DRY SATIN WATER BASED

Print date: 09.09.2015

Product code: W702739-W007

Page 6 of 6

SECTION 14: Transport information**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

Other applicable information

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): 2004/42/EG A/d 130(2010) <80g/l VOC

Additional informationDirective 2004/42/EG: compliant
1907/2006/EG REACH: compliant**National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

EUH208 Contains benz/methyl/chlormethyl-isothiazolon. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)