Report Date: 12/10/2009 REVISION DATE: 12/08/2009

REV. NO./REPL. SDS GENERATED: 1

SAFETY DATA SHEET DIRECT-TO-METAL PAINT SMOOTH FINISH

According to Regulation (EC) No 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME DIRECT-TO-METAL PAINT SMOOTH FINISH

PRODUCT NO. WK007 INTERNAL ID W018

SYNONYMS, TRADE NAMES 214321 Direct to Metal Paint Smooth Finish Black Satin, 214322 Direct to Metal Paint Smooth Finish

Silver Satin, 214323 Direct to Metal Paint Smooth Finish White Satin, 214324 Direct to Metal Paint

Smooth Finish Green Satin, 214320 Direct to Metal Smooth Finish Matt Black

APPLICATION Self priming paint for metal.

SUPPLIER Wickes Building Supplies Limited

Lodge Way House Lodge Way Harlestone Road Northampton. NN5 7UG www.wickes.co.uk

CONTACT PERSON safetydatasheet@jwo.com

EMERGENCY TELEPHONE 0844 892 2701

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

ENVIRONMENT

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Dipropylene Glycol Monomethyl Ether	252-104-2	34590-94-8	1-5%	-
Phosphonate Salt	287-243-8		1-5%	Xi;R36/38.
AMMONIA%	215-647-6	1336-21-6	< 1%	C;R34 N;R50
FORMALDEHYDE%	200-001-8	50-00-0	< 1%	Carc. Cat. 3;R40 T;R23/24/25 C;R34 R43
2-(2-BUTOXYETHOXY)ETHANOL	203-961-6	112-34-5	< 1%	Xi;R36
ZINC OXIDE	215-222-5	1314-13-2	< 1%	N;R50/53

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

Place unconscious person on the side in the recovery position and ensure breathing If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

DIRECT-TO-METAL PAINT SMOOTH FINISH

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-(2-BUTOXYETHOXY)ETHANOL		10 ppm	67.5 mg/m3	15 ppm	101.2 mg/m3	
AMMONIA%	WEL	25 ppm	18 mg/m3	35 ppm	25 mg/m3	
Dipropylene Glycol Monomethyl Ether	OES		600 mg/m3			
FORMALDEHYDE%	WEL	2 ppm	2,5 mg/m3	2 ppm	2,5 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT





PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. All handling to take place in well-ventilated area.

RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

Report Date : 12/10/2009 REVISION DATE: 12/08/2009

REV. NO./REPL. SDS GENERATED: 1

DIRECT-TO-METAL PAINT SMOOTH FINISH

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid
COLOUR Varying
ODOUR Mild

SOLUBILITY Miscible with water.

RELATIVE DENSITY 1.03 - 1.22 Approx. @20°C. VAPOUR DENSITY (air=1) Heavier than air

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Not regarded as a health hazard under current legislation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

No transport warning sign required.

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

S2 Keep out of the reach of children

S56 Dispose of this material and its container to hazardous or special waste collection point.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

Report Date: 12/10/2009 REVISION DATE: 12/08/2009

REV. NO./REPL. SDS GENERATED: 1

DIRECT-TO-METAL PAINT SMOOTH FINISH

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

16 OTHER INFORMATION

INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

ISSUED BY

HS&E Manager.

REVISION DATE 12/08/2009

REV. NO./REPL. SDS GENERATED 1

SAFETY DATA SHEET STATUS

Under preparation.

RISK PHRASES IN FULL

NC Not classified.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R34 Causes burns.
R36 Irritating to eyes.

R36/38 Irritating to eyes and skin.
R37 Irritating to respiratory system.

R40 Limited evidence of a carcinogenic effect.
R43 May cause sensitisation by skin contact.

R50 Very toxic to aquatic organisms.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.