



SAFETY DATA SHEET WICKES SUPER TOUGH WOOD FILLER

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/ UNDERTAKING

PRODUCT NAME WICKES SUPER TOUGH WOOD FILLER
PRODUCT NO. 600073/4
SYNONYMS, TRADE NAMES WN 10185
APPLICATION Wood filler
SUPPLIER Wickes Building Supplies Ltd,
Wickes House,
120/138 Station Road,
Harrow. HA1 2QB
0208 901 2000
0870 608 9001 (Customer
Services)
0208 427 1645
EMERGENCY TELEPHONE Tel 0800 731 7656
Fax: 0208 427 1645

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
STYRENE	202-851-5	100-42-5	25-50%	R10 Xn;R20 Xi;R36/38

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

A two-pack polyester resin based filler with a stabilised benzoyl peroxide catalyst.

3 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation. Irritating to eyes and skin.

CLASSIFICATION Xn;R20. Xi;R36/38. R10.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove affected person from source of contamination. Provide rest, warmth and fresh air. Place unconscious person on the side in the recovery position and ensure breathing can take place. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

General first aid, rest, warmth and fresh air. Place unconscious person on the side in the recovery position and ensure breathing. If breathing stops, provide artificial respiration. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Get medical attention if any discomfort continues.

INGESTION

Provide rest, warmth and fresh air. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove contaminated clothing. Wash skin thoroughly with soap and water. Contact physician if irritation continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

WICKES SUPER TOUGH WOOD FILLER

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Alcohol resistant foam. Carbon dioxide (CO2).

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. NOTE! Use air-supplied respirators to protect against gases/fumes. Cool containers exposed to flames with water until well after the fire is out. Move container from fire area if it can be done without risk. Keep run-off water out of sewers and water sources. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. When dealing with a spillage, please consult the section relating to suitable protective measures. Wear necessary protective equipment. Provide ventilation and confine spill. Do not allow runoff to sewer. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Wash thoroughly after dealing with a spillage. Inform Authorities if large amounts are involved.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Risk of vapour concentration on the floor and in low-lying areas. Provide good ventilation. Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. During application and drying, solvent vapours will be emitted. Avoid inhalation of vapours. Do not use in confined spaces without adequate ventilation and/or respirator.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Store at moderate temperatures in dry, well ventilated area. Store separated from: Oxidising material. Acids. Alkalies.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
STYRENE	WEL	100 ppm	430 mg/m3	250 ppm	1080 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. Must not be handled in confined space without sufficient ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Two-pack product comprising a tin containing stiff paste and a sachet of catalyst.
COLOUR	Brownish
ODOUR	Strong. Characteristic
SOLUBILITY	Immiscible with water
FLASH POINT (°C)	~ 34 CC (Closed cup).

10 STABILITY AND REACTIVITY

WICKES SUPER TOUGH WOOD FILLER

STABILITY

Stable under normal temperature conditions. No particular stability concerns.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong mineral acids. Strong alkalis. Oxidising materials.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon dioxide (CO₂). Carbon monoxide (CO). Oxides of: Nitrogen.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Knowledge about health hazard is incomplete. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea.

SKIN CONTACT

Product has a defatting effect on skin. May be absorbed through the skin.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

DEGRADABILITY

There is no data available on the product itself.

WATER HAZARD CLASSIFICATION

The product should not be allowed to enter drains or watercourses, or be deposited where it can affect ground or surface waters.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Contact specialist disposal companies.

14 TRANSPORT INFORMATION

GENERAL

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that person's transporting the product know what to do in an accident or spillage.

Limited Quantity packagings only allowed. (Special Provision 236 refers.)

No transport warning sign required.

PROPER SHIPPING NAME

Polyester Resin Kit

UN NO. ROAD

3269

ADR CLASS NO.

3

UN NO. SEA

3269

IMDG CLASS

3

IMDG PACK GR.

III

MARINE POLLUTANT

No.

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

STYRENE

RISK PHRASES

R10

Flammable.

WICKES SUPER TOUGH WOOD FILLER

R20 Harmful by inhalation.
R36/38 Irritating to eyes and skin.

SAFETY PHRASES

S2 Keep out of the reach of children
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 Wear suitable gloves.
S37/39 Wear suitable gloves and eye/face protection.
S46 If swallowed, seek medical advice immediately and show this container or label.
S51 Use only in well-ventilated areas.
S64 If swallowed, rinse mouth with water (only if the person is conscious).

UK REGULATORY REFERENCES

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation.
The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

The Manual Handling Operations Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 : CHIP 3.

The Carriage of Dangerous Goods (Classification, Packing and Labelling) and Use of Transportable Pressure Regulations 1996.

The Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations.

European Agreement concerning the International Carriage of Dangerous Goods by Road [ADR]

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45 Safety Data Sheet Directive 91/155

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Inclusion of EAN Code.

REVISION DATE 27-10-2006
REV. NO./REPL. SDS WN 10185/0
GENERATED
SDS NO. WN 10185/1

SAFETY DATA SHEET STATUS

Approved.

RISK PHRASES IN FULL

R10 Flammable.
R20 Harmful by inhalation.
R36/38 Irritating to eyes and skin.