

PAVING & PATIO SEAL

Wickes Paving and Patio Seal is a high-performance clear seal that is designed to protect, Maintain and stabilise block paving and patios. Leaving a long-lasting clear seal.

COMPOSITION

A solution of acrylic resins in aromatic hydrocarbon solvents.

PROPERTIES

Appearance – Colourless, low viscosity liquid.
Odour – Characteristic solvent type.
VOC Content – Very High (>50%w/w)
Solubility – immiscible with water.

AREAS OF APPLICATION

Suitable for Block paving, Patio slabs and Flag stones, including Cast and Limestone

PREPARATION

When treating existing paved areas ensure the surface is clean, dry and free from dust, grease and oil. If Surface is covered with dirt, moss and lichen, remove with a patio cleaner and stiff brush, rinse with water and allow to dry thoroughly. Newly laid patios should be allowed to weather for one month before applying. All paving slabs or block paving and jointing sand should be dry before application.

APPLICATION

For best results, use on a dry day above 10°C. Shake well before use, pour the tin into a roller tray and use a long pile roller to apply in long smooth strokes. On textured block paving, make sure any puddles are spread into dry areas. Apply 2 Coats allowing 4 hours between coats.

COVERAGE

Wickes Paving and Patio Seal cover approximately 6 square metres per litre, Coverage will vary depending on the texture & type of the surface you're coating.

DRYING TIME

Once applied it can be walked over after 4 hours, However it is better to leave surface 24 Hours before vehicles can be parked on treated area. Drying times are extended in colder conditions.

CLEANING OF TOOLS

Remove as much product from the application equipment before cleaning. Clean brushes, rollers and other equipment immediately after use with white spirit or brush cleaner.

MAINTENANCE

Surfaces should be routinely cleaned using a Patio & Paving Cleaner. Treated areas should be recoated approximately every 2 years depending on use.

IMPORTANT NOTES

- Always read the instructions before use
- Do not apply if air or surface temperature is below 10°C
- Don't apply if it's raining or forecast to rain
- Wickes Paving and Patio Seal may darken some block paving, it is important to pre-test on a small inconspicuous area first.
- Wickes Paving & Patio seal dries to a satin sheen. Sheen level will be dependent on the porosity of the substrate
- Caution: Surface may be slippery when wet.
- Avoid spillages onto surrounding vegetation and protect garden furniture
- Remove any splashes whilst still wet with White Spirit
- Always remove as much product as possible before cleaning equipment with White Spirit.

STORAGE

Keep container tightly closed. Observe label precautions. Store between 5 and 25°C. Keep in a cool, dry, well-ventilated place away from heat and sources of ignition and direct sunlight. No smoking. Store and transport in a secure and upright position to avoid risk of spillage.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack. Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point 44°C
Flammable product

SUPPLY

Suitable for Block paving, Patio slabs and Flag stones, including Cast and Limestone

SIZES

5 Litres

DISPOSAL

Don't empty any left over product into drains or watercourses. Dispose of contents and container in accordance with all local, regional, national and international regulations

DISCLAIMER

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.